

			
	Model	P330	
Video & Audio	Image Sensor	1/2.49" CMOS Sensor	
	Video Resolution	3840x2160 (8.0 Megapixels) at 25 frames/sec	
	Lens	f=4.0mm fixed; F=2.0, with IR-cut filter	
	Video Format	H.265	
	Field of View	Horizontal: 87°	
		Vertical: 44°	
	Day & Night	Auto-switching with IR-cut filter	
	Night Vision	30 meters (100ft) (LED: 18pcs/14mil/850nm)	
Power	Audio	2 Way Audio	
	PoE	IEEE 802.3af, 48V Active	
Interface	DC Power	DC 12.0V-1A, <12W	
	Power	DC power port	
	System	Reset button	
	Ethernet	One 10M/100Mbps; RJ45	
	Storage	MicroSD card slot (Max. 256GB)	
Software Features	Audio	Built-in microphone and Speaker	
	Frame Rate	2-25FPS	
	Code Rate	Mainstream: 4096Kbps - 8192Kbps (default: 6144Kbps)	
		Substream: 64Kbps - 512Kbps (default: 256Kbps)	
	Browser Supported	Edge, Chrome, Firefox, Safari	
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android	
	Smart Alarm	Person detection; vehicle detection; Animal detection; motion detection	
	Record Mode	Motion-triggered recording (default); scheduled recording; 24/7 recording	
Working Environment	Protocol & Standard	HTTPS, SSL, TCP/IP, UDP, HTTP, IPv4, UPnP, RTSP, RTMP, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P	
	Maximal User Access	20 Users (1 admin account & 19 user accounts); Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams)	
	Temperature	Operating temperature: -10°C - +55°C (14° F - 131° F)	
Size & Weight	Humidity	Operating humidity: 10% - 90%	
	Waterproof	IP67	
Warranty	Dimension	60 x 66 x 192mm	
	Weight	488g	
Limited Warranty@		2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/	