



GAS CONVECTION OVENS

IMPERIAL

IMPERIAL



PCVG-2

Shown with optional casters

MODEL NUMBERS

PCVG-2*

PCVDG-2

CONVECTION OVEN FEATURES

- One hand opens and closes both doors simultaneously
- 50/50 doors swing open to 130°
- Large windows
- Two interior lights
- Digital electronic controls
- Stainless steel exterior
- Rugged 1/2 HP 2 speed motor per oven
- Porcelainized oven interior for easy cleaning and better browning
- Five oven racks included with 10 rack positions
- Most spacious oven interior available
- Curved corners for easy cleaning

CONVECTION OVEN FEATURES

- Easy-to-program. Simply select the time, temperature, fan settings and hold mode, then preset buttons.
- Cook 'n Hold feature. Cooks at a higher temperature for browning. Automatically switches to a lower holding temperature.
- 24 hr. digital countdown timer with easy-to-read LED digital display.
- Cooking versatility
- Fan option lets you choose modes:
 1. Fan on continuously
 2. Fan on when heat is on pulsed fan feature.
- °F or °C readings can be displayed.

*PCVG-2 is ENERGY STAR® certified.

MANUAL CONTROLS

- Independent time and temperature controls give you maximum versatility for general baking and roasting.
- 2-speed fan switch controls bake or roast

THERMOSTATIC OVEN CONTROL

- Electronic temperature control: 150°F to 500°F (66° C to 260° C).

ON - OFF SWITCH

- 60 minute manual timer
- Audible buzzer lets you know when the cooking cycle is complete.




IMPERIAL

1128 Sherborn Street | Corona, CA 92879 | 800.343.7790 | imperialrange.com | imperialsales@imperialrange.com

©2024 Imperial Commercial Cooking Equipment Imperial reserves the right to change specifications at any time without prior notice and without any obligation for past or future equipment purchases. Visit www.imperialrange.com for specification updates



GAS CONVECTION OVENS



GAS CONVECTION OVENS

MODEL	DESCRIPTION	GAS OUTPUT BTU	GAS OUTPUT KW	SHIP WEIGHT KG	SHIP WEIGHT LBS
PCVG-2*	DOUBLE DECK, STANDARD DEPTH	140,000	41	455	1,005
PCVDG-2	DOUBLE DECK, BAKERY DEPTH	160,000	47	536	1,185

MANIFOLD PRESSURE		
NATURAL GAS	PROPANE GAS	MANIFOLD SIZE
5.0" W.C.	10.0" W.C.	3/4" (19 MM)

MODEL	DIMENSIONS	CRATED DIMENSIONS
	PCVG-2*	38" W X 41-1/2" D X 74" H (965 X 1054 X 1880 MM)
PCVDG-2	38" W X 45-1/2" D X 74" H (965 X 1156 X 1880 MM)	40" X 51-1/2" X 72" (1016 X 1308 X 1829 MM)

UTILITY REQUIREMENTS GAS MODELS			
VOLTAGE	PHASE	HZ	AMPS MAX
120	1	60/50	9

EXTERIOR

- Stainless steel exterior, except back. Reflects a quality, professional look for exhibition cooking.
- Welded and finished seams
- Stainless steel legs
- Easy to clean and maintain
- One year parts and labor warranty

OPTIONS AND ACCESSORIES

- Cook and Hold computer controls
- Stainless steel back enclosure
- Direct connect vent
- Heavy duty casters, set of 4
- Stack kit with 6" (152) stainless steel legs
- One point gas connection for double stack ovens
- Stainless steel solid doors

*PCVG-2 is ENERGY STAR® certified.



CLEARANCE REQUIREMENTS

For use only on non-combustible floors with legs or casters; or 2 1/4" (57 mm) overhang is required when curb mounted. Provide 0" clearance from non-combustible side and rear walls. Provide 6" (152mm) minimum clearance from combustible side walls and 0" from combustible wall at rear.



MADE IN USA



1128 Sherborn Street | Corona, CA 92879 | 800.343.7790 | imperialrange.com | imperialsales@imperialrange.com

© 2024 Imperial Commercial Cooking Equipment. Imperial reserves the right to change specifications at any time without prior notice and without any obligation for past or future equipment purchases. Visit www.imperialrange.com for specification updates.