


PIG® Grippy® Adhesive-Backed Floor Mat

GRP36200 High-Traction, Self-Sticking Entrance & Walkway Runner, Mediumweight, 3' x 100'

Hassling with rubber-backed floor mats or rental mats? Make the switch to the mat that sticks; our super-safe, adhesive-backed commercial floor mat creates a safe walking surface in entrances and aislesways.

- 3' x 100' mediumweight roll allows you to customize the amount of walk off and floor coverage you need to provide a high-traction walking surface in wet problem spots for customers and employees; replaces outdated rental and rubber-backed floor mats and rugs
- Place in doorways and entrances, walkways and aislesways, transition areas, breakrooms and cafeterias, along produce walls or floral displays, on production floors, ramps and loading docks, beneath water fountains, ice machines and beverage stations or under liquid hazard areas
- Adhesive-backed floor mat stays exactly where you put it with no shifting, bunching up or ripples that cause slips and trips
- Dries out quickly without moisture soaking through to the floor; absorbs water, oil and grease and traps dirt and salt to keep it from being tracked around
- Stays in place for up to 3 to 6 months, depending on conditions and traffic patterns
- Weighs less than rental and rubber-backed mats for less hassle, saves you up to 50% per year on rental contracts and has a lower environmental impact
- Easy to clean: you can sweep, vacuum, mop, use your shop/wet vac or run your floor scrubber over Grippy Mat and it won't budge
- The thinnest commercial floor mat you can buy: no rippled edges to obstruct doors or create tripping hazards. ADA compliant for wheelchairs and walkers; carts and pallet jacks roll right over it
- Sticks to most commercial floor surfaces including concrete, vinyl, linoleum, ceramic tile, quarry tile and laminate flooring
- Tested and Certified by the National Floor Safety Institute (NFSI): high-traction surfaces such as PIG Grippy Floor Mat have been



proven to reduce slip-and-fall claims by as much as 90%

- Mats take on the properties of absorbed liquids
- always take proper precautions when handling saturated absorbents



Item#	Description	Dimensions	Weight
GRP36200-BK		3' W x 100' L	25 lbs.
GRP36200-GY		3' W x 100' L	25 lbs.
GRP36200-TN		3' W x 100' L	25 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
GRP36200-BK		91.4cm W x 30m L	11.3 kg
GRP36200-GY		91.4cm W x 30m L	11.3 kg
GRP36200-TN		91.4cm W x 30m L	11.3 kg

Specifications

Style	High-Traction, Self-Sticking Entrance & Walkway Runner
Dimensions	3' W x 100' L
Mat Weight	Mediumweight
Absorbency	Up to 8 gal. per roll
Backing Material	Adhesive-Backed
Brand	PIG
Category	Grippy® Floor Mat
Core Diameter	3"
Flammability Specifications	Flame Resistant - Will melt and self-extinguish
Fluid Absorbed	Water; Grease; Oils
Incinerable	Yes
Industry	Grocery/Retail; Restaurant; Institutional & Commercial Facilities; Education; Hospitality
Indoor/Outdoor	Indoor Use
Perforated	No
Storage Temp Range	Store between 32°F and 120°F
Temperature Limit	Surface temps from 55°F to 120°F
Traffic	Heavy Foot Traffic; Carts & Equipment
UV Resistant	No

Walking Surface	Absorbent Top
Distributor Part Number	10811- 188;40ch72;45gn70;53te75;6547107;6547098;7506398;0408 8x00581
Sold as	1 roll
Weight	25 lbs.
# per Pallet	18
Composition	Absorbent - Polypropylene Adhesive Backing - Proprietary Adhesive Material
UNSPSC	47131901
Pigalog® Page Number	<u>Page 25</u>

Metric Equivalent

Absorbency	Up to 30.3 L per roll
Dimensions	91.4cm W x 30m L
Weight	11.3 kg

Technical Information

Certifications, Approvals and Ratings

ADA Compliant,NFSI Certified,ANSI B101.1- 2009

Technical Documents

[PIG Adhesive-Backed Mats](#)

[New Pig Adhesive-Backed Mat Notice](#)

[Instructions for PIG Grippy Floor Mat](#)

[Case Study – Market Basket Foods](#)

[PIG Grippy Floor Mat Savings Worksheet](#)

[PIG® Grippy® Floor Mats](#)

[29 CFR 1910.22\(a\)\(2\)](#)



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com