

Ductable Portable Unit Heater PKB-DT Series



Model Code:

PKB	48	10	-3	-T	-DT	-FM
A	B	C	D	E	F	G

A: Series

B: 20 - 208V, 24 - 240V, 48 - 480V

C: KW (10)

D: 1-Phase, 3-Phase

E: T= Mechanical Thermostat

F: DT = Duct Transition

G: FM = Floor Mount -
(2) convenience carry handles
and rubber feet.



- Duct transition collar
- High mass steel fin heat exchanger
- Built-in thermostat (40°-100°F)
- Dual carrying handles
- 4 heavy-duty rubber feet
- Long life unit bearing motor
- Fan only switch
- Patented Smart Limit Protection®
- 6ft. SO cord (no plug)
- Durable 20-gauge steel enclosure
- Non-mercury tip over switch
- Standard color: Textured gray
- 2-year limited warranty

The PKB-DT Ductable Industrial Portable Unit Heater

King's PKB-DT ductable industrial portable unit heater is constructed to hold up to the rigorous demands of jobsites or industrial facilities. These portable heaters can be ducted, to direct the heated air to required areas and are ideal for construction sites, warehouse and warehouse space heating, agriculture, events and military applications. It is the best heat source to assist in dry-out applications where dry electric heat is preferred over propane or kerosene space heaters. In addition, electric heat has no odor, flame or carbon monoxide. The high CFM and low temperature rise are also key features to make the PKB-DT the best solution for temporary large capacity heating applications.

Ordering Information

	MODEL	KW	BTUH	PHASE	VOLTS	AMPS	CFM	SIZE	SO CORD SIZE
208V	PKB2005-1-T-DT-FM	5	17.1	1	208	24.0	600	A	12/3
	PKB2007-1-T-DT-FM	7.5	25.6	1	208	36.1	600	B	8/3
	PKB2010-1-T-DT-FM	10	34.1	1	208	48.1	725	B	6/3
240/ 208V	PKB2405-1-T-DT-FM	5/3.8	17.1/12.8	1	240/208*	20.8/18.0	600	A	8/3
	PKB2407-1-T-DT-FM	7.5/5.6	25.6/19.2	1	240/208*	31.3/26.9	600	B	8/3
	PKB2410-1-T-DT-FM	10/7.5	34.1/25.6	1	240/208*	41.7/36.1	725	B	6/3
	PKB2412-1-T-DT-FM	12.5/9.4	42.7/32.0	1	240/208*	52.1/45.1	825	C	6/3
480V	PKB4805-1-T-DT-FM	5	17.1	1	480	10.4	600	A	14/3
	PKB4807-1-T-DT-FM	7.5	25.6	1	480	15.6	600	B	14/3
	PKB4810-1-T-DT-FM	10	34.1	1	480	20.8	725	B	12/3
	PKB4812-1-T-DT-FM	12.5	42.7	1	480	26	825	C	10/3
208V	PKB2005-3-T-DT-FM	5	17.1	3	208	13.9	600	C	8/3
	PKB2007-3-T-DT-FM	7.5	25.6	3	208	20.8	600	C	10/4
	PKB2010-3-T-DT-FM	10	34.1	3	208	27.7	725	C	8/4
240/ 208V	PKB2405-3-T-DT-FM	5/3.8	17.1/12.8	3	240/208*	12.0/10.5	600	C	12/4
	PKB2407-3-T-DT-FM	7.5/5.6	25.6/19.2	3	240/208*	18.0/15.5	600	C	12/4
	PKB2410-3-T-DT-FM	10/7.5	34.1/25.6	3	240/208*	24.1/20.8	725	C	10/4
	PKB2412-3-T-DT-FM	12.5/9.4	42.7/32.0	3	240/208*	30.1/26.1	825	C	8/4
480V	PKB4805-3-T-DT-FM	5	17.1	3	480	6.0	600	C	14/4
	PKB4807-3-T-DT-FM	7.5	25.6	3	480	9.0	600	C	14/4
	PKB4810-3-T-DT-FM	10	34.1	3	480	12.0	725	C	14/4
	PKB4812-3-T-DT-FM	12.5	42.7	3	480	15.0	825	C	12/4

*Dual rated heaters will draw 13% less amps and 25% less wattage when operated at 208V.

Ductable Portable Unit Heater PKB-DT Series

Engineering Specifications

Contractor shall supply and install PKB-DT Series ductable portable unit heaters manufactured by King Electrical Mfg. Company. Heaters shall be of the wattage and voltage as indicated on the plans.

Construction: All exterior and interior metal enclosure parts are made from 20 gauge electrogalvanized Steel with a rust inhibiting baked enamel finish. Smooth rounded corners and protective edge trim give an attractive modern appearance.

Built-in Thermostat: Single pole factory installed hydraulic capillary tube thermostat for precision heating control. Operating range 40° to 100

Fan Only Switch: Comes standard with fan-only switch.

Duct Transition: Comes standard with a 12" duct transition to allow for connection of ducting (optional). A duct reducer can be added (purchased separately) to allow for a minimum of 8" ducting on all models, except 12.5KW where 12" minimum duct size is required. Ducting should not exceed 25 Foot in length.

Rear Intake Screen: Heavy gauge steel screen protects against foreign objects making accidental contact with the rotating fan blade.

Spiral Fin Elements: The metal sheath element is copper brazed with spiral fins then molded into a coil configuration. This combination produces the best

heat transfer while eliminating the potential for hot spots by positioning the element in the maximum airflow stream.

Totally Enclosed Fan Motor: Permanently lubricated long life, unit bearing with 20cc of oil. Epoxy-coated motor with enclosed rotor resists moisture and corrosion for long-lasting, trouble-free operation.

Aluminum Fan Blade: Axial flow-type fan mounted directly to the motor shaft for maximum efficiency.

Thermal Overload: Heaters shall be equipped with King's patented thermal overload Smart Limit Protection®, which disconnects elements and motor in the event normal operating temperatures are exceeded. If thermal overload trips due to abnormal operating temperatures, thermal overload shall remain open until manually reset by turning the heater off for 15 minutes. Automatically reset of thermal overloads, which allow the element to continue to cycle under abnormal conditions, will not be accepted.

Cord Length: 6 Foot SO Cord (No Plug Provided)

Approvals: cETLus (517271) & (30314521)

Options/Accessories

ADD SUFFIX	DESCRIPTION
-25C	25 foot cord option

Dimensional Data

HEATER SIZE	DIMENSIONS			
	HEIGHT	DEPTH	WIDTH	DT1
A	16.5"	11"	15.1"	12"
B	16.5"	13.5"	15.1"	12"
C	16.5"	18"	15.1"	12"

Minimum Clearance

front.....	3 ft.
top.....	1 ft.
sides.....	1 ft.
rear.....	1 ft.

