

PMM60A 60W RMS P.A. power mixer amplifier

PMM120A 120W RMS P.A. power mixer amplifier

Features

Speco Technologies' UL listed Contractor Series amplifiers are designed for long-running, every day use. They can stand on their own to run a smaller installation, or be incorporated into a much larger job. With RMS power ranging from 30W to 120W, microphone and source-mixing ability, telephone paging interface and music-on-hold capability, there's practically no job where one of these amplifiers wouldn't be a perfect fit!



Speaker Specifications		
Model	PMM120A	PMM60A
RMS Output Power	120W	60W
Max Output Power	180W	90W
AC Power Consumption	850W	670W
Power Supply	AC 120V, 50/60Hz	
Zones	1	
Speaker Outputs	4/8/16 Ohms, 70/25V	
Inputs	3 x Mic (XLR), 1 x Mic (XLR or Terminal), 3 x Mic/Aux (Terminal or Stereo RCA), 1 x EQ/Mix (RCA) 1 x Tel (Terminal)	
Frequency Response	50Hz ~ 15KHz (±3dB)	
Tone Control	Bass ± 10dB, Treble ± 10dB	
THD	Less than 1% @ 1KHz	
Signal/Noise Ratio	Microphone: >60dB TEL: >60dB Line: >70dB	
Controls	Volume for each source, Master Volume. Vox Sensitivity	
Telephone	TEL in and MoH Out	
Indicators	Power, power level	
Dimensions	16.9" (W) x 3.5" (H) x 11.8" (D)	
Weight	23.6lbs.	19lbs.
Listings	UL, cULm CE, FCC	

NDAA
COMPLIANT

*Products are in compliance with NDAA Section 889 Part B Guidelines

Optional Accessories



PBMRK2
Rack Mounting Kit