

PROJECT
TYPE
CATALOG #

02-PRLEDCNYXTE

NEW YORK CITY APPROVED LED EXIT & EMERGENCY COMBO

HOUSING

- Durable powder-coated 20-gauge steel construction in white or black finish.
- Injection-molded, engineering grade, high-impact, thermoplastic heads.
- Field removable steel knockout chevron directional indicators on exit face.

ELECTRICAL

- Dual 120 / 277V voltage.
- Charge rate / power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 9.6V maintenance-free, rechargeable NiCd battery.
- Internal solid-state transfer switch automatically connects the internal battery to LED board and lamp heads for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.
- Remote capable standard.

ILLUMINATION

- Adjustable 1.5W square LED lampheads with long lasting & efficient ultra bright white LEDs.
- Field installable third emergency lighting head included with the 02-PRLEDCNYXTE-43 model.
- Knockouts provided on sides of unit to relocate lamp heads.
- High performance chrome-plated metallized reflector and plastic lens for optimal light distribution.
- Ultra bright, energy efficient, long life Red LEDs.
- New York City compliant 8" EXIT letters.

MOUNTING

- Knockouts on the back for wall mount.
- Mounting hardware provided for ceiling (2-head model) or end mount.
- Knockouts provided for conduit feed applications.

CODE COMPLIANCE

- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for damp locations (0°C - 50°C)

WARRANTY

- 5-year warranty on all electronics and housing.
- Battery pro rated for five years.



Model	Size (inches) & Weight (lbs)			
	L (in)	W (in)	H (in)	Weight
02-PRLEDCNYXTE	9-5/8	2-3/4	12-1/8	



PRODUCT PARAMETERS

MODEL	NO. OF FACES		LETTER COLOR		HOUSING COLOR		TOTAL NO. OF HEADS (INTEGRAL + REMOTE*)		NO. OF INTEGRAL HEADS	
02-PRLEDCNYXTE	3	Universal Single/ Double Face	R	Red	W	White	4	4 Heads	2	2 Heads
									3	3 Heads

NOTES: * Using 1.5W LED remote heads.



PROJECT
TYPE
CATALOG #

02-PRLEDCNYXTE

NEW YORK CITY APPROVED LED EXIT & EMERGENCY COMBO

ELECTRICAL INFORMATION

CATALOG NUMBER	INPUT WATTS (W)		INPUT AMPS (A)		BATTERY	REMOTE CAPACITY
	120V	277V	120V	277V		
02-PRLEDCNYXTE	5.2	6.2	0.06	0.04	9.6V	1.5W-3W

DIMENSIONAL DRAWINGS

