

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :		
Model # :		
Item # :	Qty:	
Available W/H :		
Approval :		

Glass & Solid Half Door Refrigerator

Reach-In Top Mount PRÔ Series

Model: PRO-77R-GSH-N

🚐 FEATURES & BENEFITS ≕

Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

■ Digital temperature control & monitor system

- · Keep food products safe by maintaining constant temperatures.
- · Alarms that sound when doors are not sealed shut; protect against food spoilage that originates from cold air leaks.
- · Early warning alarm program detects issues before malfunction occurs.
- Digital display allows for easy monitoring.
- Programs interpret the condition of refrigeration systems by self-diagnosis.
- · Automatic evaporator fan motor delays.

■ Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet the new standards of the EPA and DOE in 2017. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Cold air distribution system

Provides uniformly maintained temperature within the food zone.

All stainless steel cabinet construction

The PRO series model boasts all stainless steel interior and exterior (galvanized steel top, bottom and back). It guarantees the utmost in cleanliness and long product life. The PRO series model adds a touch of style to the most refined setting.

Sturdy, clean stainless steel shelving

Shelves are the most important part of cleanliness as they come in direct contact with food. After a while, PVC coated wire shelves may peel, rust and lead to unsanitary conditions. Only the Turbo Air PRO series uniquely provides stainless steel shelving.

■ Door pressure release device

Pressure relief doors are designed to eliminate vacuum pressure and allow easy, instant door opening.

■ High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

■ LED interior lighting

- Top mount compressor
- Refrigerator holds 33°F ~ 38°F for the best in food preservation



Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.











Model PRO-77R-GSH-N	Door	66.2	Shelves	7/8	5.5	Weight (lbs.) 796	(inches) 773/4 x 337/8 x 78
Model	Swing	CII/FT	#of	ПР	AMDS	Crated Weight (the)	$L \times D^{\dagger} \times H^{\dagger}$

(unit: inch)

Glass & Solid Half Door Refrigerator

Model: PRO-77R-GSH-N

ELECTRICAL DATA						
Voltage	115/60/1					
Plug Type	① NEMA 5-15P					
Full Load Amperes	5.5					
Compressor HP	7/8					
Feed Wires with Ground	3					
Cord Length (ft.)	9					
Refrigerant	R-290					
DIMENSIONAL DATA						
# of Doors	6					
# of Racks Accepted	3					
Net Capacity (cu. ft.)	66.2					
Ext. Length Overall (in.)	77 _{3/4} (1976mm)					
Ext. Depth Overall (in.)*	337/8 (860mm)					
Ext. Height Overall (in.)†	78 (1981mm)					
Int. Length Overall (in.)	737/8 (1876mm)					
Int. Depth Overall (in.)	291/2 (750mm)					
Int. Height Overall (in.)	58 _{3/4} (1493mm)					
Net Weight (lbs.)	708					
Gross Weight (lbs.)	796					
# of Shelves	9					
Shelf Size (L x D) (in.)	23 x 251/4 (Left/Right)					
	251/4 x 251/4 (Middle)					

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

- * Depth does not include 1-1/8" for door handles.
- † Height does not include 5" for caster height.


3 Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor


- Anti-corrosion coated evaporator
- Door locks standard
- Self-contained system
- Standard 4" dia. swivel casters with locks on the front set
- Easy replaceable one piece magnetic door gaskets
- Solid and sturdy grille design
- Legs available (optional)
- Half size pan racks available (optional)

■ OPTIONAL ACCESSORIES:

- ☐ 5" caster, ½" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- ☐ 6" stainless steel leg: 30221M0600
- ☐ Additional stainless steel shelf: SP8F180100 (Left/Right), SP8F180200 (Middle)
- ☐ Half door bun tray rack: TSP-2224 (each holds up to six 18"L x 26"D sheet pans)

PLAN VIEW





SIDE VIEW

■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519

■ Warranty: 800-381-7770 ■ AC: 888-900-1002

Ver.20171010

5 YEAR WARRANTY



NATURAL







