



**PROMAX** is used dilute concentrated products, using a “Venturi tube” system. The advantage of these systems is the water/chemical mixing that creates a product which is ready to use.

**Promax** is an automatic dilution system that requires no current or power supplies of any kind, the suction is created from the force of the water supply.

**Promax** finds its greatest application in the dilution of concentrated products suitable for cleaning and disinfecting surfaces. The most common applications and the recommended Promax models are as follows:

- **Filling bottles: Promax 4l/min**
- **Filling buckets: Promax 16l/min**
- **Filling tanks and floor washers: Promax 16-30l/min**

The products used in these applications can be: Odour removers, Glass and multi-surface cleaners, Degreasers, Concentrated cleaners, Deep-cleaning foaming products, Sanitizers, Ammonia, Deodoriser cleaners, Floor and multi-surface cleaners, Multi-surface degreasers ...etc

## TECHNICAL FEATURES:

<b>Water supply connection</b>	Possible from right or left		
<b>Type of connection</b>	¾" Female GHT or GAS		
<b>Type of disconnection</b>	F-Gap (Flexible membrane)		
	A-Gap (Physical, Visible Gap)		
<b>Venturi flow rates</b>	1 GPM (4 LPM) (Gray)	4 GPM (16 LPM) (Yellow)	8 GPM (30 LPM) (Blue)
<b>Actuating systems</b>	Slide		
<b>No. of product inlets</b>	1product		
<b>Working pressure</b>	<b>Min 15 PSI (1bar)</b>		<b>Max 130 PSI (9bar)</b>
	<b>Ideal: 30 – 60 PSI (2 – 4bar)</b>		
<b>Water temperature</b>	<b>40 – 160 °F (5 – 70 °C)</b>		
<b>Notes</b>	Possibility of adding modules after installation		
<b>Environment temperature</b>	40 – 120 °F (5 – 50 °C)		
<b>Storage temperature</b>	-4 – 140 °F (-20 – 60 °C)		

## PACKAGING:

- Dispenser
- Pick up tube - 13ft (4 m)
- Discharge hose 6.5ft (2 m) for 16-30lt/min (4 - 8 GPM) or “S” shaped discharge tube for 4lt/min (1 GPM) spray bottle fill
- Hose Hanger (only if hose 6.5ft is present)
- Complete installation kit:
  - Plastic clamps (2 pcs)
  - Metering tips (1 bag)
  - Foot filter and non-return valve assembly (1 pcs)
  - Ceramic weight (1 pcs)
  - Anchors (3pcs)
  - Screws (3pcs)
  - Washers (3pcs)
  - Coupler (for ganging two or more units together)
  - ¾" male GHT Fitting- ¾" male GHT Fitting
  - Adhesive Labels for container identification (1 chart)
  - Adhesive Labels for product identification (1 chart)

# PROMAX SLIDE 1 PRODUCT



## DISPENSER KEY CODE

<b>1-2</b>	<b>NAME</b>	
<b>PX</b>	PROMAX	
<b>3</b>	<b>ATTIVATION METHOD</b>	
<b>S</b>	SLIDE	
<b>4</b>	<b>NUMBER OF PRODUCTS</b>	
<b>1</b>	1 PRODUCT	
<b>5</b>	<b>TYPE OF BACKFLOW PREVENT</b>	
<b>F</b>	FLEX GAP	
<b>A</b>	AIR GAP	
<b>N</b>	NO GAP	
<b>6-7</b>	<b>FLOWRATE</b>	
<b>04</b>	4 LPM (1 GPM)	
<b>16</b>	16 LPM (4.2 GPM)	
<b>30</b>	30 LPM (7.9 GPM)	
<b>8</b>	<b>MARKET</b>	
<b>U</b>	USA	
<b>S</b>	EUROPE (STD)	
<b>V</b>	UK	
<b>C</b>	CHINA	
<b>J</b>	JAPAN	
<b>K</b>	NETHERLAND/BELGIUM	
<b>9-12</b>	<b>CUSTOMIZATION</b>	
<b>0000</b>	Standard	

  

PX	S	1	F	16	U	0000
----	---	---	---	----	---	------

## VENTURI CHARACTERISTICS

The dilution ratio refer to the dynamic pressure of 40 PSI (2,76bar) with water thin products.

STANDARD METRING TIP	Tip color	Diameter mm
	Notip	\
	Grey	3.25
	Black	2.54
	Beige	1.78
	Red	1.32
	White	1.09
	Blue	1.01
	Tan	0.88
	Green	0.71
	Orange	0.63
	Brown	0.58
	Yellow	0.51
	Aqua	0.46
	Purple	0.36
	Pink	0.25
Clear	\	

ULTRALEAN TIP	Lime	0.228
	Burgundy	0.208
	Pumpkin	0.168
	Copper	0.155

The dilution ratio refer to the dynamic pressure of 40 PSI (2,76bar) with water thin products.

STANDARD METRING TIP	Tip color	Diameter mm
	Notip	\
	Grey	3.25
	Black	2.54
	Beige	1.78
	Red	1.32
	White	1.09
	Blue	1.01
	Tan	0.88
	Green	0.71
	Orange	0.63
	Brown	0.58
	Yellow	0.51
	Aqua	0.46
	Purple	0.36
	Pink	0.25
Clear	\	

ULTRALEAN TIP	Lime	0.228
	Burgundy	0.208
	Pumpkin	0.168
	Copper	0.155

### Flex-Gap

4 lt/min Model			
Oz/Gal	grit	%	Ratio
50.1	411.7	41.2	24 : 1
46.6	382.7	38.3	2.6 : 1
43.7	369.0	35.9	2.8 : 1
32.3	265.8	26.6	3.8 : 1
20.1	165.2	16.5	6.1 : 1
13.0	106.8	10.7	9.4 : 1
11.5	94.8	9.5	10.6 : 1
8.7	71.2	7.1	14.0 : 1
6.1	49.9	5.0	20.0 : 1
5.1	42.2	4.2	23.7 : 1
3.4	28.1	2.8	35.6 : 1
3.3	27.1	2.7	36.9 : 1
2.6	21.6	2.2	46.3 : 1
1.3	11.0	1.1	90.9 : 1
0.7	5.5	0.6	181.8 : 1
No hole			

14 lt/min Model			
Oz/Gal	grit	%	Ratio
21.6	177.3	17.7	5.6 : 1
20.8	171.0	17.1	5.9 : 1
19.5	160.1	16.0	6.3 : 1
14.4	118.2	11.8	8.5 : 1
9.2	75.3	7.5	13.3 : 1
6.0	49.4	4.9	20.2 : 1
5.2	42.7	4.3	23.4 : 1
3.9	31.8	3.2	31.5 : 1
2.3	19.0	1.9	52.6 : 1
1.8	14.6	1.5	68.5 : 1
1.5	12.5	1.3	80.0 : 1
1.3	10.4	1.0	96.2 : 1
1.0	8.3	0.8	120.5 : 1
0.6	4.6	0.5	217.4 : 1
0.3	2.5	0.3	400.0 : 1
No hole			

0.52	4.30	0.43	233 : 1
0.37	3.00	0.30	333 : 1
0.28	2.30	0.23	435 : 1
0.19	1.60	0.16	625 : 1

0.26	2.10	0.21	476 : 1
0.19	1.60	0.16	625 : 1
0.15	1.20	0.12	833 : 1
0.10	0.80	0.08	1250 : 1

### Flex-Gap

30 lt/min Model			
Oz/Gal	grit	%	Ratio
5.4	44.6	4.5	22.4 : 1
5.3	43.5	4.4	23.0 : 1
5.2	42.6	4.3	23.5 : 1
3.8	31.2	3.1	32.1 : 1
2.5	20.4	2.0	49.0 : 1
1.7	14.0	1.4	71.4 : 1
1.5	12.0	1.2	83.3 : 1
1.2	9.5	1.0	105.3 : 1
0.8	6.3	0.6	158.7 : 1
0.7	5.6	0.6	178.6 : 1
0.5	4.2	0.4	238.1 : 1
0.4	3.6	0.4	277.8 : 1
0.3	2.6	0.3	384.6 : 1
0.15	1.2	0.1	833.3 : 1
0.12	1.0	0.1	1000.0 : 1
No hole			

0.09	0.70	0.07	1429 : 1
0.06	0.50	0.05	2000 : 1
0.04	0.30	0.03	3333 : 1
0.02	0.20	0.02	5000 : 1

# PROMAX SLIDE 1 PRODUCT



The dilution ratio refer to the dynamic pressure of 40 PSI (2,76bar) with water thin products.

## Air-Gap

STANDARD METERING TIP	Tip color	Diameter mm
	No tip	\
	Grey	3.25
	Black	2.54
	Beige	1.78
	Red	1.32
	White	1.09
	Blue	1.01
	Tan	0.88
	Green	0.71
	Orange	0.63
	Brown	0.58
	Yellow	0.51
	Aqua	0.46
	Purple	0.36
	Pink	0.25
	Clear	\

4 lt/min Model			
Oz/Gal	gr/lt	%	Ratio
38.8	319.0	31.9	3.13 :1
38.7	318.0	31.8	3.14 :1
37.9	311.2	31.1	3.2 :1
30.8	253.3	25.3	4.0 :1
21.9	179.6	18.0	5.6 :1
14.7	120.9	12.1	8.3 :1
12.7	104.2	10.4	9.6 :1
8.7	71.1	7.1	14.1 :1
6.7	55.1	5.5	18.2 :1
5.1	42.0	4.2	23.8 :1
4.3	35.5	3.6	28.2 :1
3.8	31.5	3.2	31.8 :1
2.8	23.0	2.3	43.5 :1
1.6	13.0	1.3	76.9 :1
0.8	6.5	0.7	153.9 :1
No hole			

16 lt/min Model			
Oz/Gal	gr/lt	%	Ratio
15.6	128.2	12.8	7.80 :1
15.5	127.7	12.8	7.83 :1
12.5	102.8	10.3	9.7 :1
12.0	98.5	9.9	10.2 :1
9.4	77.3	7.7	12.9 :1
6.3	51.6	5.2	19.4 :1
5.5	45.2	4.5	22.1 :1
4.5	36.8	3.7	27.2 :1
3.1	25.7	2.6	38.9 :1
2.3	19.0	1.9	52.6 :1
2.2	18.1	1.8	55.3 :1
1.8	14.8	1.5	67.6 :1
1.5	12.0	1.2	83.3 :1
1.1	8.7	0.9	114.9 :1
0.7	5.5	0.6	181.8 :1
No hole			

ULTRALEAN TIP	Line	0.228
	Burgundy	0.208
	Pumpkin	0.168
	Copper	0.155

0.51	4.20	0.42	238 :1
0.40	3.30	0.33	303 :1
0.34	2.80	0.28	357 :1
0.29	2.40	0.24	417 :1

0.21	1.70	0.17	588 :1
0.16	1.30	0.13	769 :1
0.12	1.00	0.10	1000 :1
0.09	0.70	0.07	1429 :1

## DIMENSIONS

