



## Regency 3 Bowl Underbar Sink with Faucet and 2 Drainboards - 60" x 18 3/4"

#60B31014213K



### Technical Data

Length	60 Inches
Width	18 3/4 Inches
Height	33 Inches
Drainboard Length	13 Inches
Spout Length	10 Inches
Bowl Depth	10 Inches
Backsplash Height	3 Inches
Faucet Height	5 1/2 Inches
Work Surface Height	30 Inches
Backsplash	With Backsplash

### Features

- Durable stainless steel construction
- Three 2" drains (1 1/2" IPS) with drain baskets included
- Galvanized legs with plastic bullet feet
- 10" swing spout, 2 GPM aerator
- Two drainboards aid in fast drying

### Certifications



NSF Listed



1/2" Water Connection

## Technical Data

Bowl Front to Back	14 Inches
Bowl Left to Right	10 Inches
Drainboard Location	Left Drainboard Right Drainboard
Faucet Centers	4 Inches
Features	Faucet Included
Flow Rate	2 GPM
Gauge	16 - 18 Gauge
Leg Construction	Galvanized Steel
Material	Stainless Steel
Maximum Water Temperature	140 Degrees F
Number of Compartments	3 Compartments
Number of Drainboards	2 Drainboards
Spout Clearance	3 1/4 Inches
Spout Type	Swing
Stainless Steel Type	Type 304
Type	Bar Sinks
Water Inlet Size	1/2 Inches

## Notes & Details

This Regency 3 bowl underbar sink comes standard with three bowls, making it great for a standard wash, rinse, and sanitize operation. The deep 10" sink bowls accommodate all types of barware, including pitchers! As an added convenience, it features a 3" high backsplash to keep your bar better protected from accidental spills. The drainboards feature a grooved surface to help hold onto your barware as the excess water drains downward into the sink.

This sink offers a durable 18-gauge type 304 stainless steel construction along its top, bowls, and back. For maximum stability, it has 16-gauge galvanized steel legs with plastic bullet feet. This sink includes a chrome-plated brass faucet with 1/2" NPS inlets and a 10" swing spout that releases water through a 2 GPM aerator, creating a soft flow pattern with minimal splashing. The faucet has a 140-degree Fahrenheit maximum water temperature. Three 2" drains (1 1/2" IPS) with drain baskets are included.

The included faucet uses ceramic cartridges, which provide a much lower fail rate than the compression cartridges widely used in the industry. In this design, 2 ceramic discs fit together to create a watertight seal when closed. This removes the need for a rubber seat washer, which is one of the most frequently replaced parts on a faucet. The sturdy lever handle design makes it easy to turn the water flow off and on.

### Kit Includes:

- 3 bowl underbar sink with 2 drainboards - 60" x 18 3/4"
- Wall mount faucet with 10" swing spout

**⚠ WARNING:** This product can expose you to chemicals including lead, which are known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information, go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).