




SlowStop® Rebounding Bollard – 6” (SS6Y-42)



Color: RAL 1023 Safety Yellow Bollard
RAL 9005 Black Base

Diameter: 6.63” (6” ANSI Schedule 40)
Height: 42”

Set Screws: 8 M16 x 2.00
8mm Hex

Cap: Black Plastic

MASS (LBS)	5000	7500	10000	15000	20000	25000	30000	40000	80000
SPEED (MPH)									
1.0									
1.5									
2.0									
2.5									
3.0									
3.5									
4.0									
4.5									
5.0									
5.5									
6.0									
6.5									
7.0									

Installs with eight (8) 5/8” x 5-1/2”
Concrete Screw Anchor s

No Damage / Negligible Damage
Will Stop / Potential Damage to Guard
Guard is under-sized

SPECIFICATIONS

- Stopping Power: 25,868 joules / 19,072 ft-lb.
- No Damage Rating: 12,934 joules / 9,536 ft-lb.
- Meets IBC 1607.8.3 requirements to resist 6,000 pounds of force at 27” height
- Temperature Rating: -40°
- Pipe Coating: 60µm Hot Dipped Galvanized + 60µm Polyester Outdoor Powder Coat
- Cast Iron Coating: Environmentally Friendly Water-Based KTL Coating + Powder Coat C5I Rated

RECOMMENDED USES

- Heavy Duty
- Loading Docks and Warehouse Entrance Ramps
- Equipment and Storage Rack Guarding
- Utility Protection
- Pedestrian Safety
- Access Denial
- Post-tensioned Concrete
- Not for K-Rated Security Use



4955 Stout Dr. • San Antonio, TX 78219
210-736-4477 • 800-736-5256 • Fax 210-734-6448
Email: info@slowstop.com
www.slowstop.com



QR: Download Spec Sheets
©2021 SlowStop. All rights reserved.