



SlowStop® StoreFront Bollard (SS5Y-42-SF, SS5S-42-SF)

- Certified: F3016 Independently Tested 5,000 pounds at 10.4 mph
- Color: RAL 1023 Safety Yellow Bollard (Stainless Steel Available)
RAL 9005 Black Base
- Diameter: 5.56" (5" ANSI schedule 40)
Height: 42" (44" overall with cap)
- Set Screws: 5 M16 x 2.00 (8mm hex)
1 M16 x 35mm (hex head)
- Cap: Cast Aluminum



See Testing Video at www.slowstop.com



Installs easily with six (6) 3/4" x 5-1/2" Concrete Screw Anchors

SPECIFICATIONS

- Stopping Power: 5,000 pounds @ 10.4 mph—No Damage
- Meets IFC 312.3 requirement to resist 12,000 pounds at 36" height
- Meets IBC 1607.8.3 requirements to resist 6,000 pounds of force at 27" height
- Temperature Rating: -40°

RECOMMENDED USES

- StoreFront Parking Applications
- Protect Rear Entrance Doors, Stairs
- Around Sign Columns, Fire Hydrants
- Guard Air Stations
- Kiosk Protection
- On Concrete Slabs—min. 6" - 3,000 PSI
- Add Plastic Bollard Covers for Brand Coloring
- Ideal for Store Retrofits



4955 Stout Dr. • San Antonio, TX 78219
210-736-4477 • 800-736-5256 • Fax 210-734-6448
Email: info@slowstop.com
www.slowstop.com



QR: Download Spec Sheets
©2021 SlowStop. All rights reserved.