		Project Name:		AIA#:	
	Model #:	Location:			
SIS#:		Item #:	Quantity:		
Oloin.		Rom #1	Quality		



10 Quart Planetary Bench Mixer

The Perfect Mix of Value. Performance & Durability

Features front mounted touch pad control panel with 60-minute digital timer!









Model

□ SP10

Standard Features

- Powerful 1/3 HP custom built motor
- Gear-driven, high-torque transmission
- Heat-treated hardened steel alloy gears & shafts
- Three fixed speeds
- Permanently lubricated transmission
- Thermal overload protection
- Front-mounted touch pad controls with 60minute digital timer and last-batch recall
- Removable stainless steel, interlocking bowl guard with built-in fully welded ingredient chute
- Interlocked bowl lift
- Rigid cast iron body
- Industry standard #12 attachment hub
- NSF approved enamel gray paint
- 6-foot cord and ground plug

Standard Accessories

- 10 qt (#304 series) stainless steel bowl
- Aluminum flat beater
- Stainless steel wire whip
- Aluminum spiral dough hook
- Non-slip rubber feet

Warranty


Two year parts and labor


Optional Accessories


- Slicer/shredder/grater for #12 hub
- Meat grinder for #12 hub
- Stainless steel flat beater
- Stainless steel spiral dough hook
- Mixer table with undershelf
- Extended warranty

To select options, see complete list on back

Approved by:	Date:







UNIT: INCHES (CM)

Drawings available through KCL at www.kclcad.com.

DIMENSIONS & SHIPPING INFORMATION

Carton reinforced for shipping. The weight and dimensions of this reinforced carton are included below and may vary from shipment to shipment. This product ships on a pallet. Freight class 85.

-		-		1	
Model	Base Foot Print	Overall Dimensions	Net Wt	Shipping Dimensions	Shipping Wt
SP10	15" w x 15.5" d	16.3" w x 17.7" d x 31" h	135 lbs	32" w x 40" d x 42" h	245 lbs
31 10	(38 cm x 39 cm)	(41 cm x 45 cm x 79 cm)	(60 kg)	(81 cm x 102 cm x 107 cm)	(111 kg)

Cord & Plug: Attached 6-foot flexible 3-wire cord with molded plug fits a grounded receptacle. NEMA 5-15P (!,)

SPECIFICATIONS												
Model	Motor	Volts	Amps	Transmission Type	Capacity	Controls	Agitate 1st	or Speeds 2nd	(RPMs) 3rd	Attach 1st	nment Speed	ds (RPMs) 3rd
SP10	1/3 HP	115/60/1	5	Gear	10 qt 9 liter	Front-mounted digital controls & timer	104	194	353	59	110	201

Mixer is constructed of a rigid cast iron body with front-mounted controls and a digital 60-minute timer with last-batch recall. Mixer has a 1/3 HP custom built motor with overload protection and gear-driven, high torque permanently lubricated transmission consisting of heattreated hardened steel alloy gears and shafts. Mixer comes with 10 qt. stainless steel bowl, aluminum flat beater, stainless steel wire whip, and aluminum dough hook and non-slip rubber feet. Interlocked with removable stainless steel bowl guard with fully welded on ingredient chute. Mixer has #12 attachment hub and interlocked bowl lift. Mixer is NSF and ETL listed. Two year parts and labor warranty.

OPTIONAL MIXER ACCESSORIES AND HUB ATTACHMENTS:

M	IXER.
	XXB

- OWL-10 stainless steel (S/S) bowl ■ XXBEAT-10 Aluminum flat beater
- ☐ XXBEAT-10SS S/S flat beater
- ☐ XXHOOK-10 Alum. spiral dough hook ☐ XXHOOK-10SS S/S spiral dough hook
- ☐ XXWHIP-10 S/S wire whip
- XXHDWHIP10-4 Heavy-duty 2 mm S/S wire whip
- ☐ XTable S/S countertop mixer table with under shelf (30" W x 24" D x 24" H)

HUB:

■ XVSGH 9" Slicer/Shredder/Grater housing only (no plates included-must select from plates listed on this sheet)

- ☐ XASP Adjustable slicing plate (for vegetables only)
- ☐ XPH Plate holder -*only 1 required

Shredding Plates:

- ☐ XSP332* 3/32" $(2.3 \, \text{mm})$ ☐ XSP316* 3/16" (4.7 mm)
- ☐ XSP14* 1/4" (6.3 mm) ■ XSP516* 5/16" (7.9 mm) **■ XSP12*** 1/2" (12.7 mm)
- ☐ XGP* Grating plate ■ XMCA-SS Meat grinder assembly
 - (Polished stainless steel cylinder, worm gear, ring, and s/s pan. Includes knife, 3/16" plate, and pusher.)
- XXCK Chopper knife for the XMCA-SS

Chopper Plate Sizes Available:

- ☐ CP02-12 1/16" (2 mm) ■ CP04-12 5/32" (4 mm) ☐ CP05-12 3/16" (5 mm) ☐ CP06-12 1/4" (6 mm) ☐ CP08-12 5/16" (8 mm) ☐ CP10-12 3/8" (10 mm) ☐ CP12-12 1/2" (12 mm)
- ☐ CP14-12 9/16" (14 mm ☐ CP16-12 5/8" (16 mm)
- ☐ CP18-12 11/16" (18 mm) ☐ CP00-12 Stuffing plate
- ☐ XST12 1/2" Stuffing tube (mutton) ☐ XST34 3/4" Stuffing tube (pork)

☐ FACTORY INSTALLED OPTION:

XXCORR-10 Correctional package, includes tamper resistant external fasteners.

☐ EXTENDED WARRANTY

SP-XD1020 Extended warranty for SP10 mixer, extends factory warranty to 2-years. Available only at time of purchase.