

# DIRECT DRAW DISPENSER - LESS TOWER



PRO-LINE™ 25" - 1 KEG

- Designed by beer-industry experts for performance and value.
- Rugged keg slide - extends floor life.
- Full-size drain tray - larger work area and improved hygiene.
- Commercial grade construction - built to last.
- Digital thermostat.



**MDD23-E-LT**  
Black



**MDD23S-E-LT**  
Stainless Steel



Listed by Edison Testing Laboratories.  
Conforms to UL & NSF Standards.

[www.micromatic.com](http://www.micromatic.com) • 1 (866) 327-4159

PRO-LINE™ 25" - 1 KEG

Job Number: \_\_\_\_\_ Location: \_\_\_\_\_

Part No.	Finish	Doors	Shipping Weight
<input type="checkbox"/> MDD23-E-LT	Black	1	78 kg 172 lbs
<input type="checkbox"/> MDD23S-E-LT	Stainless Steel	1	78 kg 172 lbs

## Operating Performance

Capacity of 1/2 Kegs	1	Running Amps	1.5
Cubic Feet (liters)	8.4 (239)	Voltage	115/60/1
Approval	ETL Listed	Plug Type	NEMA-5-15P
Compressor HP	1/10	Cord Length	8'
Thermostat	Digital	Refrigerant	R290
Working High/Low Pressure	300 psig / 150 psig	Charge oz	2.8

Exterior	All Models: 18 gauge stainless steel top, 22 gauge solid doors, 24 gauge steel front, sides and back. Black Vinyl Models: Front, sides. Stainless Steel Models: Front, sides
Interior	20 gauge stainless steel floor, reinforced frame, 24 gauge galvanized walls
Ventilation	Back ventilated
Plumbing	Drain Tray: 3/4" NPT drain includes hose and drain bottle. Automatic condensate evaporator, no drain connection required. Evaporator condensate has been plumbed to a condensate pan located in the compressor housing.
Insulation	Foamed-in-place using high density, CFC-free polyurethane; 2" top, walls and floor.
Casters	Standard

## Dimensions

