

PBM30 30W P.A. Amplifier

Features

Speco Technologies' UL listed Contractor Series amplifiers are designed for long-running, every day use. They can stand on their own to run a smaller installation, or be incorporated into a much larger job. With RMS power ranging from 30W to 120W, microphone and source-mixing ability, telephone paging interface and music-on-hold capability, there's practically no job where one of these amplifiers wouldn't be a perfect fit!

Speaker Specifications

Model	PBM30
RMS Output Power	30W
Max Output Power	45W
AC Power Consumption	500W
Power Supply	AC 120V, 50/60Hz
Zones	1
Speaker Outputs	4/8/16 Ohms, 70/25V
Inputs	2 x Mic (Terminal), 1 x Aux (Stereo RCA)
Frequency Response	70Hz ~ 18KHz (±3dB)
Tone Control	50Hz ~ 15KHz (±3dB)
THD	Less than 1% @ 1KHz
Signal/Noise Ratio	Microphone: >55dB TEL: >60dB Line: >70dB
Controls	Volume for each source, Tone, TEL Input Level
Telephone	TEL in and MoH Out
Indicators	Power
Dimensions	10.75" (W) x 3.5" (H) x 9.5" (D)
Weight	11.4lbs.
Listings	UL, cULm CE, FCC



NDAA
COMPLIANT

*Products are in compliance with NDAA Section 889 Part B Guidelines