

Our Shrink Wrapping Plug-and-Go Unit



- Compact size
- Micro Knife Technology Seals PVC or POF
- Magnetic Hold Down
- Dual Mode Switch (Seal only or Seal & Shrink)
- Heavy Duty Plexiglass Hood
- Adjustable Table Lowers 2" for High Products

More Details:

This unique "All-In-One" L-Bar Sealer and Shrink Chamber features new "Micro Knife Technology" which can seal PVC and POF shrink films. With the dual magnet hold down, the operator simply lowers the hooded chamber and the magnets apply the seal pressure to produce great seals and eliminate

operator fatigue. The magnets hold the chamber closed during the shrink cycle and releases when the shrink cycle is complete. Complete cycle time is approximately 5-10 seconds.

Option available for SS-48ST in 220V.

Features:

	SS-48ST-110V	SS-76ST	SS-77ST
Power Supply	110V / 1 PH / 20 AMPS	220V / 1 PH / 25 AMPS	220V / 1 PH / 30 AMPS
Watts	1650W	3000W	3000W
Seal Dimensions	12"W x 18.5"L	16"W x 22"L	20"W x 30"L
Machine Dimensions	50"L x 26"W x 45"H	56"L x 30"W x 45"H	72"L x 35"W x 50"H
Max Film Width	20"	24"	28"
Max Package Height	6"	8"	10"
Production Rate	3-5 PPM	3-5 PPM	3-5 PPM
Weight	270-LBS	350-LBS	400-LBS