

Great general purpose shrink tunnel for variety of applications



Standard Features:

- Fully Re-Circulating Air Chamber
- Live Roller Rod Conveyor
- Digital Temperature Control (0-400°F)
- State of the Art AC Variable Speed Drive 0-75FPM
- Chromed Conveyor Rollers and Shaft (No Rust)
- Automatic Tunnel Cool Down with Shut Off
- 1HP Blower Motor
- Sealed Bearings on Drive and Idler Shafts
- Chamber Size: 36”W x 60”L with various heights
- Quietest Tunnel on the Market
- Heats up to 300°F in less than 15 minutes
- Thermal Overload Protection on All Motors
- Locking Casters with Leveling Screws
- Anti-Jam Safety Feature on Conveyor
- 15 KW Heater Bank
- 1-year Warranty

Optional Features:

- 12”, 16”, 20”, 24”, or 28” Tunnel Height
- Close Roller Spacing ½” Gap
- PTFE Mesh Belt
- Stainless Steel Metal Mesh Belt

The ST-36-60-series shrink tunnel is a great general purpose shrink tunnel that can be used for a wide variety of applications. Can be used with shrink bands, neck bands, full body sleeves, used with shrink film, used as drying or curing tunnel, etc.

SPECIFICATIONS	ST-3612-60	ST-3616-60*	ST-3620-60*
POWER	220V / 3 PHASE / 50 AMPS	220V / 3 PHASE / 50 AMPS	220V / 3 PHASE / 50 AMPS
TUNNEL DIMENSIONS (L X W H)	60” X 36” X 12”	60” X 36” X 16”	60” X 36” X 20”
SPEED	0-75 FPM	0-75 FPM	0-75 FPM
WEIGHT (NET / GROSS)	600-LBS / 800-LBS	630-LBS / 830-LBS	660-LBS / 840-LBS
MACHINE DIMENSIONS (L X W X H)	85” X 44” X 77”	85” X 44” X 81”	85” X 44” X 86”


**Special Order Only*

SHRINK TUNNEL – HIGH CAPACITY


Model: ST-36-60-Series




Falcon Belting



PTFE Mesh Belting



Stainless Steel Metal Belting



High Density Rollers – Close Roller Spacing
– 1/2" Gap



Variable Speed
Control
0-75FPM



Variable Air
Velocity



Adjustable Leveling Pads



Digital Temperature Control



Lighted Viewing Window

8820 Baird Avenue • Northridge, CA 91324 • T: 818-718-8818 • F: 818-718-8857

✉ contact@sealersales.com

💻 www.sealersales.com