



A Series Solid Door Reach-In Refrigerators & Freezers

MODEL #178A12RHC

CABINET CONSTRUCTION

White painted aluminum interior and type 430 stainless steel exterior.
Foamed-in-place CFC- and HCFC-free polyurethane insulation.
Removable one-piece grill for cleaning and servicing.
Door has stay-open feature beyond 90° for easy loading; self-close under 90° to save energy.
"No stoop" lower shelf raises product to a higher level for easy access.

REFRIGERATION SYSTEM

Environmentally-safe R290 refrigerant.
Bottom-mounted condensing unit positioned for easy maintenance.

SHELVING

3 gray epoxy-coated steel shelves included.
Each accommodates up to 90 lb.

MODEL FEATURES

Preprogrammed digital controls feature auto-defrost function

PROJECT: _____
MODEL: _____ SERIAL#: _____
ITEM #: _____ QUANTITY: _____
APPROVAL: _____ DATE: _____

A SERIES REACH-IN REFRIGERATOR

Keep ingredients within a safe temperature range in a sleek, durable, and easy-to-clean environment

SPECIAL FEATURES

- Compact, narrower width and depth that fits in small footprints
- Self-closing door with convenient stay-open feature
- Easy-to-clean 430 series stainless steel exterior
- Painted aluminum interior
- Temperature range of 33-40°F
- 3 shelves included
- Environmentally-safe R290 refrigerant
- Digital temperature controller with automatic defrost function
- 115V, 1/6 hp
- ETL Safety & Sanitation Listed



WARRANTY

RESIDENTIAL: Avantco assumes no liability for parts or labor coverage for component failure, factory defect or any other damages for units installed in non-commercial foodservice or residential applications.




Parts & Labor



Compressor



★ Conforms to UL & NSF-7 Standards



TECHNICAL DATA

Dimensions

Exterior Dimensions	24 ¹³ / ₁₆ "W x 23 ⁷ / ₁₆ "D x 64 ¹ / ₁₆ "H
Interior Dimensions	20 ⁷ / ₈ "W x 18 ⁷ / ₈ "D x 48 ³ / ₈ "H
Net Volume	11 cu. ft.
Net Weight	159 lb.
Gross Weight	183 lb.
Packaging Dimensions	26 ¹ / ₄ "W x 25 ⁵ / ₈ "D x 68 ⁷ / ₈ "H

Construction

Exterior Material	430 Stainless Steel
Interior Material	Painted Aluminum
Insulation Material	Foamed-In-Place Polyurethane
Shelf Size	(3) 17 ³ / ₄ " x 20 ¹ / ₄ "
Shelf Material	Epoxy-Coated Steel
Shelf Load Capacity	90 lb.

Cooling

Temperature Range	33°F - 40°F
Refrigerant	R290
Max. Ambient Temperature	90°F
Defrosting	Automatic
Temperature Controller	Digital
Horsepower	1/6

Electrical

Voltage	115
Amps	1.9
Hz	60
Phase	1
Plug Type	NEMA 5-15P
Electrical Cord Length	98"

PLAN VIEW

