

# 36", 42", & 48" TPI Commercial Belt Drive Portable Blowers



**WARNING:** This product can expose you to chemicals including nickel which is known to the State of California to cause cancer, and chromium, which is known to the State of California to cause birth defects and/or reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).



### Features

- Rotary switch
- SJT type cord - 3 conductor - 8' long
- Aluminum blade
- Spiral wire front and rear guards
- Powder coated 20 gauge steel housing
- 5" rubber wheels
- Meets OSHA standards / 1 Year limited warranty
- Imported to TPI specifications

### Motor Specification

- 2-Speed
- 120V
- Ball bearing
- 1-Phase
- ODP type
- Permanently lubricated

### Standard Models

MFG CATALOG NUMBER	MFG MODEL NUMBER	MOTOR HP	CFM*		VELOCITY PROFILE	MAX AMPS	WT. (LBS)	LIST
			HIGH	LOW	CFM / Area Sq Ft			
08734702	CPB 36-B	1/3	5,400	4,600	8600 / 300	4.8	82	<b>776</b>
08706602	CPB 42-B	1/2	7,600	6,700	12000 / 320	6.5	93	<b>995</b>
08722702	CPB 48-B	3/4	8,800	7,700	14000 / 500	9.0	129	<b>1346</b>

\*Measured 2 feet from face of fan

Note: Photograph is a representation of stocked models. Actual model may vary in appearance

# 24", 30", & 36" TPI Commercial Direct Drive Portable Blowers



**WARNING:** This product can expose you to chemicals including nickel which is known to the State of California to cause cancer, and chromium, which is known to the State of California to cause birth defects and/or reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).



### Features

- Rotary switch
- SJT type cord - 3 conductor
- Spiral wire front and rear guards
- Powder coated 20 gauge steel housing
- 5" rubber wheels
- Meets OSHA standards
- 1 Year limited warranty
- Imported to TPI specifications

### Motor Specification

- 2-Speed
- 120 Volt
- Ball bearing
- 1-Phase
- Open ventilated
- Permanently lubricated

### Standard Models

MFG CATALOG NUMBER	MFG MODEL NUMBER	TYPE	MOTOR HP	CFM*		VELOCITY PROFILE	MAX AMPS	CORD LENGTH	SWITCH	BLADES	WT. (LBS)	LIST
				HIGH	LOW	CFM / Area Sq Ft						
08753502	CPB 30-D	Standard / Floor	1/5	4,400	3,800	6700 / 250	3.6	6'	Rocker	Aluminum	52	<b>575</b>
08710302	CPBS 30-D	Standard / Swivel	1/5	4,400	3,800	6700 / 250	3.6	6'	Rocker	Aluminum	60	<b>654</b>
08722602	CPB 36-D	Standard / Floor	1/3	5,400	4,600	8500 / 300	3.6	10'	Rotary	Steel	70	<b>712</b>
08770102	CPBS 24-DHV	High Velocity / Swivel	1/6	3,400	2,900	5400 / 240	2.4	9'	Rotary	Aluminum	38	<b>289</b>

\*Measured 2 feet from face of fan

Note: Photograph is a representation of stocked models. Actual model may vary slightly in appearance