

IP 15W IP Ceiling Speaker

SPIPC6A

IP Speaker

SPIPC6AM

IP Speaker with Built-in Mic

Features

- Works with Speco Audio Manager Software
- Compatible with SecureGuard® VMS via ONVIF
- Supports pre-recorded messages, schedules, and alarm trigger
- Two-way audio support with mic input*
- PoE or 12/24VDC

*SPIPC6AM only



Audio

Codec	OPUS 48kHz, MP3 44.1kHz, G.722 ADPCM 16kHz, G.711 PCMU 8kHz, G.711 PCMA 8kHz
-------	------------------------------------------------------------------------------------

Speaker

Max Sound Pressure Level	96dB
Frequency Response	100Hz-18kHz
Low Frequency Range	500-2KHz 3 10dB
High Frequency Range	400-12KHz 3 20dB
Harmonic Distortion	0.1@1kHz
Signal to Noise Ratio	91dB

Network

Security	Password protection, IP address filtering, digest authentication, user access log, firewall
Network Protocol	SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP
Network Interface	10/100 Base-TX, RJ45 Support for SIP protocol for integration with VoIP systems, integrated with SIP/PBX.
VoIP	2 SIP Accounts, SIP Direct IP Call, RTP Multicast Codec: OPUS, MP3, G.722, PCMU, PCMA

Audio Specification

Inputs	(2) Alarm Inputs
--------	------------------

Microphone

Built-in MIC	SPIPC6A: No SPIPC6AM: Yes
--------------	------------------------------

General

Material	Metal
Operating Temperature	-22°F - 140°F
Operating Humidity	5% - 85%
Rate Power	15W
Power Supply	PoE or 12-24V
Dimensions	7.9" (Dia.) x 3.5" (D)
Net Weight	2.2 lbs
Package Includes	Network Ceiling Speaker User Manual
Net Weight	2.20 lbs
Package Includes	IP Horn Speaker User Manual
Color	White

