

Project:	
Item #:	Quantity:
Model #:	



SRS-2-181 (110-240 Volt / US)



Induction Cooking Station

Unit contains two (2) SM-181R, MAX Induction[™] flush-mounted induction ranges, surrounded by a #304, 18-gauge stainless steel housing, with adjustable, leveling legs.

Unit can be used for demonstration cooking, or can be used as 'hold-only' ranges for keeping food at proper holding temperature.

Perfect application for tabletop buffets, suite service, private parties or display cooking. Controls face the Operator or Chef.

[EC] Electric Requirements:

Model	Voltage	Phase	Hertz	Watts	Amps	Plug
Two (2) SM-181R	110-120 Volt/US	1	50-60	1800 Watts Each Range	15 Amps Each Range	Two (2) NEMA 5-15P 3-Prong (6' Cord)

Notes & Conditions:

- 1. Ensure that you have dedicated power wherever you are planning to use your induction range. Refer to the Installation & Operation Manual for detailed instructions regarding power requirements & operating instructions.
- 2. MAX InductionTM Ranges require use of ferrous metal, induction-ready cookware.
- 3. Approximate dimensions are 33.50" W x 20.125" D x 6" H.
- 4. Approvals: FCC, ETL, ETL to NSF4

Due to continuous product improvement, specifications are subject to change without notice