

**ARCHITECTURAL & ENGINEERING SPECIFICATION**

Exposed, quiet piston-type, chrome plated flushometer valve with a polished exterior. Complete with Zurn's MetroVantage chloramine resistant filtered by-pass. The valve incorporates a 6VDC motor actuator, a battery powered automatic sensor, high impact resistant polycarbonate housing and chrome plated plastic cover with manual override push button and 10 degree angled sensor.

**PRODUCT FEATURES**

- Control Stop has internal siphon-guard protection, sweat solder kit, wall flange with set screw.
- High back pressure Vacuum Breaker with one piece hex coupling nut
- Chloramine resistant Internal seals
- Adjustable tailpiece
- Spud coupling and flange for top spud connection
- True mechanical override button

**COMPLIANCE AND CERTIFICATION:**

- ADA Compliant
- WaterSense Compliant



This product should be used with a WaterSense labeled counterpart with a compatible flow volume to ensure that the entire system meets the requirements for water efficiency and performance.



**FLOW OPTIONS**

	FLUSH VOLUME GPF	WATERSENSE* COMPLIANT
<b>-ULF</b>	0.125	<input checked="" type="checkbox"/>
<b>-EWS</b>	0.5	<input checked="" type="checkbox"/>
<b>-WS1</b>	1.0	<input type="checkbox"/>

**VALVE HEIGHT OPTIONS**

	DIMENSION A INCH [MM]	DIMENSION B INCH [MM]
<b>-STANDARD</b>	11 1/2" [292]	9 3/16" [233]
<b>-1</b>	16" [406]	13 11/16" [348]
<b>-2</b>	24" [610]	21 11/16" [551]
<b>-3</b>	27" [686]	24 11/16" [627]

**SUFFIX OPTIONS**

- YJ Split Ring Pipe Support
- YK Solid Ring Pipe Support

ARCHITECTURAL & ENGINEERING APPROVAL

The information contained in this document is subject to change without notice. Please contact Zurn for most up to date information.

**Rough-in/Overview dimensions:**

