



Profit from the Eagle Advantage®

Specification Sheet

Short Form Specifications

Eagle Solid Shelving, model _____. (Heavy gauge stainless steel, Valu-Master® Gray epoxy, Valu-Gard® Green Epoxy, or Galvanized Steel) with raised "V" edge on all sides and double-hem bending for added strength. Aluminum corner castings to lock shelves to posts with tapered (plastic or aluminum) split sleeves.



solid shelves and posts combined to form unit

Options / Accessories

- ☐ Casters with bumper
- ☐ Foot plates
- ☐ Joining clamps
- ☐ Aluminum split sleeves
- ☐ Solid shelving ledge
- ☐ Solid shelving divider

EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA

Phone: 302-653-3000 • Fax: 302-653-2065

www.eaglegrp.com

Foodservice Division: Phone 800-441-8440

MHC/Retail Display Divisions: Phone 800-637-5100

For custom configuration or fabrication needs, contact our SpecFAB® Division.

Phone: 302-653-3000 • Fax: 302-653-2065 • e-mail: quotes@eaglegrp.com

Item No.: _____
Project No.: _____
S.I.S. No.: _____

Solid Shelving

MODELS:

- | | | | |
|--------------------------------|--------------------------------|--------------------------------|--------------------------------|
| ☐ SS14* | ☐ P7-* | ☐ P54-* | ☐ P96-* |
| ☐ SS18* | ☐ P14-* | ☐ P63-* | |
| ☐ SS21* | ☐ P18-* | ☐ P74-* | |
| ☐ SS24* | ☐ P33-* | ☐ P86-* | |

* See charts for complete model numbers.

- Solid shelving is hemmed, has a two-fold thickness of heavy gauge steel, and comes standard with a marine edge providing unsurpassed strength and stability. Aluminum corner castings create the locking mechanism to fasten the shelves to the posts.
- Raised marine edge on all four sides retains contents to shelf, makes cleaning easier and helps reduce the spill of shelf contents.
- Numerically-calibrated grooved posts, tapered plastic or aluminum split sleeves and aluminum corner castings combine to make shelf assembly fast and easy.
- Shelving can be vertically adjusted on 1" (25mm) increments for the entire post length.
- Heavy gauge stainless steel, galvanized steel coated with Valu-Master® pewter gray epoxy or Valu-Gard® green epoxy, or galvanized steel.
- Leveling feet are provided to help compensate for uneven floor surfaces.

Certifications / Approvals



Government specifications
MIL-S-40144E

AUTOQUOTES



EG01.01 Rev. 02/17

Spec sheets available for viewing, printing or downloading from our online literature library at www.eaglegrp.com

Eagle Foodservice Equipment, Eagle MHC, SpecFAB®, and Retail Display are divisions of Eagle Group. ©2017 by the Eagle Group



Profit from the Eagle Advantage®

Item No.: _____
 Project No.: _____
 S.I.S. No.: _____

Solid Shelving

Solid Shelves

galvanized	Valu-Master®	Valu-Gard®	stainless steel	width x length		weight	
				in.	mm	lb.	kg
SS1424G	SS1424V	SS1424VG	SS1424S	14" x 24"	356 x 610	10	4.6
SS1430G	SS1430V	SS1430VG	SS1430S	14" x 30"	356 x 762	12	5.5
SS1436G	SS1436V	SS1436VG	SS1436S	14" x 36"	356 x 914	14	6.4
SS1442G	SS1442V	SS1442VG	SS1442S	14" x 42"	356 x 1067	15	6.8
SS1448G	SS1448V	SS1448VG	SS1448S	14" x 48"	356 x 1219	17	7.7
SS1454G	SS1454V	SS1454VG	SS1454S	14" x 54"	356 x 1372	20	9.1
SS1460G	SS1460V	SS1460VG	SS1460S	14" x 60"	356 x 1524	22	10.0
SS1472G	SS1472V	SS1472VG	SS1472S	14" x 72"	356 x 1829	26	11.8
SS1824G	SS1824V	SS1824VG	SS1824S	18" x 24"	457 x 610	11	5.0
SS1830G	SS1830V	SS1830VG	SS1830S	18" x 30"	457 x 762	14	6.4
SS1836G	SS1836V	SS1836VG	SS1836S	18" x 36"	457 x 914	16	7.3
SS1842G	SS1842V	SS1842VG	SS1842S	18" x 42"	457 x 1067	18	8.2
SS1848G	SS1848V	SS1848VG	SS1848S	18" x 48"	457 x 1219	20	9.1
SS1854G	SS1854V	SS1854VG	SS1854S	18" x 54"	457 x 1372	22	10.0
SS1860G	SS1860V	SS1860VG	SS1860S	18" x 60"	457 x 1524	24	10.9
SS1872G	SS1872V	SS1872VG	SS1872S	18" x 72"	457 x 1829	28	12.7
SS2124G	SS2124V	SS2124VG	SS2124S	21" x 24"	533 x 610	13	5.9
SS2130G	SS2130V	SS2130VG	SS2130S	21" x 30"	533 x 762	15	6.8
SS2136G	SS2136V	SS2136VG	SS2136S	21" x 36"	533 x 914	18	8.2
SS2142G	SS2142V	SS2142VG	SS2142S	21" x 42"	533 x 1067	21	9.5
SS2148G	SS2148V	SS2148VG	SS2148S	21" x 48"	533 x 1219	23	10.5
SS2154G	SS2154V	SS2154VG	SS2154S	21" x 54"	533 x 1372	25	11.4
SS2160G	SS2160V	SS2160VG	SS2160S	21" x 60"	533 x 1524	28	12.7
SS2172G	SS2172V	SS2172VG	SS2172S	21" x 72"	533 x 1829	30	13.6
SS2424G	SS2424V	SS2424VG	SS2424S	24" x 24"	610 x 610	15	6.8
SS2430G	SS2430V	SS2430VG	SS2430S	24" x 30"	610 x 762	17	7.7
SS2436G	SS2436V	SS2436VG	SS2436S	24" x 36"	610 x 914	19	8.6
SS2442G	SS2442V	SS2442VG	SS2442S	24" x 42"	610 x 1067	23	10.5
SS2448G	SS2448V	SS2448VG	SS2448S	24" x 48"	610 x 1219	24	10.9
SS2454G	SS2454V	SS2454VG	SS2454S	24" x 54"	610 x 1372	27	12.3
SS2460G	SS2460V	SS2460VG	SS2460S	24" x 60"	610 x 1524	31	14.1
SS2472G	SS2472V	SS2472VG	SS2472S	24" x 72"	610 x 1829	33	15.0



For cleanroom applications, add prefix **CR** to stainless steel model number (ex: **CRSS1424S**).

Electropolished finish available for stainless steel shelves. Consult factory. Please note: Shelf with electropolished finish will have a flat surface without "V" edge.

Contact factory for availability of 72"-long shelves. Availability based on application.

Posts

Numerically grooved in 1" (25mm) increments. Includes post cap and leveling bolt. For mobile application (excluding 96" posts), add prefix "**C**" to model number. Example: **CP14-E**. See Spec Sheet #EG01.05 for information about casters available.

EAGLE brite***	chrome	Valu-Master®	Valu-Gard®	EAGLE gard®*	stainless steel	height		weight	
						in.	mm	lb.	kg
P7-Z	P7-C	P7-V	P7-VG	P7-E	P7-S	7"	178	1.0	0.5
P14-Z	P14-C	P14-V	P14-VG	P14-E	P14-S	14"	356	1.0	0.5
P18-Z	P18-C	P18-V	P18-VG	P18-E	P18-S	18"	457	1.5	0.7
P33-Z	P33-C	P33-V	P33-VG	P33-E	P33-S	33"	838	2.0	0.9
P54-Z	P54-C	P54-V	P54-VG	P54-E	P54-S	54"	1372	3.0	1.4
P63-Z	P63-C	P63-V	P63-VG	P63-E	P63-S	63"	1600	3.5	1.6
P74-Z	P74-C	P74-V	P74-VG	P74-E	P74-S	74"	1880	4.0	1.8
P86-Z	P86-C	P86-V	P86-VG	P86-E	P86-S	86"	2184	5.0	2.3
- n/a -	P96-C***	- n/a -	- n/a -	- n/a -	P96-S***	96"	2438	6.0	2.7

* MICROGARD® standard on all EAGLEgard® posts.

** EAGLEbrite® posts are clear epoxy coated for use in dry or wet environments.

*** 96" (2538mm) posts are NOT to be used on units less than 24" (610mm) front-to-back. Recommend using in conjunction with foot plates to affix to floor, and with post clamps where applicable. For stationary use only!



EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA

Phone: 302-653-3000 • Fax: 302-653-2065

www.eaglegrp.com

Foodservice Division: Phone 800-441-8440

MHC/Retail Display Divisions: Phone 800-637-5100

Spec sheets available for viewing, printing or downloading from our online literature library at www.eaglegrp.com

Although every attempt has been made to ensure the accuracy of the information provided, we cannot be held responsible for typographical or printing errors. Information and specifications are subject to change without notice. Please confirm at time of order.

Printed in U.S.A.
 ©2017 by Eagle Group
 Rev. 02/17