Airmovers

Stealth AV3000 Airmover

High velocity, long-throw airflow. Ventilates smoke, dust and fumes and dries large spaces fast. Direct air anywhere – easily reposition the airmover on its versatile integrated stand. The Stealth's advanced blade design delivers quieter operation AND higher intensity airflow. Variable speed control for easy airflow adjustments.

Features

- Integrated stand provides ultimate control direct airflow at walls, floors or ceilings
- Low-noise StealthTM fan blades for quieter operation
- Variable speed to customize airflow and noise levels
- Power outlet socket for daisy-chaining up to four units on a single 15A circuit
- Hour meter
- Circuit breaker and reset switch
- Secure, nested stacking up to 5 high
- Rugged carry handle and integrated cord wrap

Specifications

- Air movement: 2600 CFM | 4417 CMH
 Static pressure: 0.40 in. (H₂O) | 99 Pa
- Circuit maximum: Up to 4
- **Dimensions (D × W × H)**: $10.8 \times 24.3 \times 24.0$ in. | $27.4 \times 61.7 \times 61.0$ cm
- Weight: 27.5 lbs. | 12.5 kg
- Amps: 2.7A
 Volts: 115V
 Frequency: 6
- Frequency: 60Hz
- Power: 0.46HP / 340W (motor rating)
- Sound level (avg.): 58–72 dB
- Control: Variable speed rotary switch
- Cord length: 15 ft. | 4.6 m
- **Construction**: Rotomolded polyethylene and injection molded ABS housing components; steel wire inlet and outlet grills.
- Safety: ETL listed to UL/cUL and CSA Standards
- Xactimate: WTRDRY+

Sizes • Options

• 113164 (F568): One unit