STI UNIVERSAL











PRODUCT OVERVIEW

These indoor/outdoor low profile or dome polycarbonate covers protect devices such as pull stations, keypads for entry systems, intercom stations, emergency buttons, electrical light switches, duplex plugs, etc., without restricting legitimate operation. The versatile cover offers excellent protection against physical damage (both accidental and intentional), dust and grime as well as severe environments inside and out.

Cover options: Dome or Low Profile, with or without piezo horn, flush mount, surface mount or waterproof back box models. Maximum protrusion is 4 inches deep. Cover has the same footprint as the Mini Stopper® but accommodates most dual action pull stations.



KEY FEATURES

General Information

- · Protects against vandalism, accidental damage, dust and grime and severe environments inside and outside.
- · Protects pull stations, keypads, intercom stations, emergency buttons, electrical light switches or duplex plugs.
- · ADA Compliant.
- · Three year guarantee against breakage of polycarbonate in normal use (one year on electro mechanical and electronic components).

Design

- · Top and bottom of waterproof back box are threaded for 3/4" NPT rigid conduit.
- · Sized to fit most pull stations.
- · High strength continuous hinge.

Construction

- · Cover is molded from thick, tough polycarbonate material.
- · UV-stabilized to keep cover clear.

Installation

- · Gaskets included.
- · Typical working properties of polycarbonate are -40° to 250°F (-40° to 121°C).

Electronics

- · Models STI-13x30 and STI-14x30 have optional relay output with 12-24 VDC power input.
- · Available with or without 105 dB horn (flashes on STI-14000 models).

Options

- · Cover available in low profile or dome shape.
- · Flush frame, surface frame or waterproof back box (with sealed or open internal mounting plate), enclosed flush back box.
- · Locking tab (not for use with fire pull stations).
- · Available with red, green, blue, yellow, white or black label hood/horn housing with custom or no label.
- · Available for red units "In Case of Fire..." label.



STI Universal Stopper®

Dimensions and Technical Information

BUILD YOUR MODEL STI-1 **Cover Options** 3 = Dome4 = Low Profile (horn models flash) **Mounting Options** 0 = Flush Mount 2 = Surface Mount 3 = Enclosed Flush Back Box 4 = Enclosed Back Box & Sealed Mounting Plate* 5 = Enclosed Back Box & Opened Mounting Plate* 8 = Enclosed Back Box & European Sealed Mounting Plate* 9 = Enclosed Back Box & European Open Mounting Plate* *all colors except NC Hood/Horn 00 = No Label Hood (Label must start with 'N.' If Hood/Horn Option = 0 and Mounting Option = 0 or 3, the label must be NC) 10 = Label Hood without Horn* 20 = Label Hood with Horn* (low profile flashes) 30 = Label Hood with Horn & Relay* (low profile flashes) *all colors except NC

Hood/Horn Color & Label

Fire label	Free Custom label*
FR = Red Fire label	CK = Black*
No label	CB = Blue*
NK = Black	CG = Green*
NB = Blue	CR = Red*
NG = Green	CW = White*
NR = Red	CY = Yellow*
NW = White	
NY = Yellow	
NC = Clear (not available for bood/born options 10, 20, 30)	

*Custom labels (including spaces)

13000 Series 2 lines, Line 1 (C1), Line 2 (C2), 40 characters each 14000 Series 2 lines, Line 1 (C1), Line 2 (C2), 30 characters each

Accessories Available

AUUCUUUII	es Available	WAI
STI-1314	Universal Stopper Backplate	Thre
STI-1331	1 1/2" (37mm) Spacer	norn
STI-6602	Horn Label housing for 13000 series – fire label	com
STI-6602-*	Horn Label housing for 13000 series – no text	
STI-6602-C*	Horn Label housing for 13000 series – custom text	
KIT-1402	Horn Base Assembly for 14000 series, black only (purchase top shell separate	ly)
KIT-1403	Horn Label Shell for 14000 series - Fire label	
KIT-1403-N*	Horn Label Shell for 14000 series - no text	
KIT-1403-C*	Horn Label Shell for 14000 series - custom text	
KIT-319	Replacement wiring harness for remote power/relay models STI-13x30 and ST	I-14x3
KIT-320	Replacement wiring harness with grommet for enclosed back box options	
KIT-65	Breakaway Seal (qty. 5)	
KIT-EA135	Service Pin for models with sounder	
STI-6004	Weather Gasket - fits 1/2" or 3/4" conduit, closed cell neoprene	
KIT-G01331	Gasket for add-on spacer	
KIT-G01307	Gasket for hinged spacer. May be replaced with form-in-place gasket on space	r and
	1/8" diameter gaskets for conduit area	
KIT-M06540	Replacement red housing for 13000 series - fire label	
KIT-M06540-	* Replacement housing for 13000 series - no text (custom text available)	

COVER OPTIONS - SIDE VIEW





Dome

Low Profile (horn models flash)

MOUNTING OPTIONS







Enclosed Flush









With Sealed **Mounting Plate**

With Opened **Mounting Plate**

BACK BOX With European Sealed **Mounting Plate**

BACK BOX With European Opened **Mounting Plate**

APPROVAL & WARRANTY

TESTING

· ADA Compliant

Tested and approved or listed by:

- · UL/cUL Listed No. S2466 (NEMA Type 3RX mounting options 3, 4, 5, 8, 9).
- · IP56 (cover 3, mounting options 4, 5, 8, 9).

WARRANTY

ee year guarantee against breakage of polycarbonate in mal use (one year on electro mechanical and electronic nponents).

IMPORTANT NOTICE

When used on fire systems, Universal Stopper is intended for areas where the incidence of false fire alarms from manual pull stations is high or has proven to be a serious problem. Any disadvantage of the device is more than balanced when one considers the consequences of false fire alarms, especially if fire service personnel and equipment are responding to a false fire alarm when they are needed for a real fire somewhere else. Add to this the disruption to the facility when false alarms occur. If you have, or may have, a problem with false fire alarms or physical/weather damage to your fire alarm activation devices, the Universal Stopper could prove invaluable.

*Add letter to indicate color: R=red, G=green, B=blue, Y=yellow, W=white, or K=black



2306 Airport Road info@sti-usa.com Waterford, MI www.sti-global.com 48327. USA Tel:248-673-9898

Taylor House 34 Sherwood Rd., Bromsgrove, www.sti-global.com Worcs., B60 3DR, England

info@sti-emea.com Tel: +44 (0) 1527 520 999 Unit 7A Lockheed Avenue Airport Business Park Waterford X91 HWF2 Ireland