APPLICATION:			PRODUCT NAME:		
				STAINLESS STEEL SWIVEL SPOUT ASSEMBLY	——————————————————————————————————————
JOB NAME:				SPECIAL CONFIGURATION CHECK BASE MODEL AND OPTIONS	700
QUANTITY:	ITEM NO.		MODEL:		
			□ 54380	6" SWIVEL SPOUT	
			□ 54399	8" SWIVEL SPOUT	
			□ 54402	10" SWIVEL SPOUT	
"B"			□ 54410	12" SWIVEL SPOUT	
			□ 54429	14" SWIVEL SPOUT	
			□ 54445	16" SWIVEL SPOUT	
			OPTIONS C	OR MODIFICATIONS:	
			□ OTHER		
			FEATURES		

MODEL	DIM "A"	DIM "B"	DIM "C"
54380	6"	3/8"	4"
	[152mm]	[10mm]	[102mm]
54399	8"	1-1/4"	5"
	[204mm]	[33mm]	[127mm]
54402	10"	1-1/4"	5"
	[254mm]	[33mm]	[127mm]
54410	12"	2"	5 - 3/4"
	[305mm]	[51mm]	[145mm]
54429	14"	2 - 5/8"	6-1/4"
	[356mm]	[67mm]	[160mm]

3-1/4"

[83mm]

[178mm]

16"

[406mm]

54445

- "A" -

RECOMMENDED	SETTINGS

* 2.2 GPM AERATOR

* 110°F AT 80 PSI

SYSTEM LIMITS

FEATURES

- * TEMP: 40°F MIN. TO 140°F MAX.
- * PRESSURE: 200 PSI MAX. STATIC

SHIPPING WEIGHT

- * 0.75 LBS
- * NSF 61-9 APPROVED & LISTED www.truesdail.com



TOLL FREE: 800-421-6162 - FAX: 800-832-8238 information@fisher-mfg.com - www.fisher-mfg.com