



UNIVERSAL

T755 & T751 THERMOSTATS



T751



T755

UNIVERSAL T755 & T751

Simple. Affordable. Professional.



Up to 4 Heat, 2 Cool Heat Pump - Up to 2 Heat, 2 Cool Conventional
Auto-changeover - 7" Display - Dual Fuel Capable Through Logic Without Sensors

7D 7 Day Programmable 5/1/1 5/1/1 Programmable NP Non-Programmable Model #			Stages Of Heat	Stages Of Cool	Heat Pump Systems With Auxiliary	Conventional Systems	PTAC Mode	Display Size (square inches)	Filter Change Reminder	Room Temperature Calibration	Adjustable Heat & Cool Temperature Swing	Programmable Fan	Adjustable Setpoint Limits	Auto Changeover	Memory Type (permanent)	Remote Sensor Capable	Outdoor Temperature Sensor Capable	WiFi Ready	Fan Speeds	Warranty (years)	Terminals
T751		NP	4*	2	•	•	•	7	•	•	•	•	•	•					3	5	Rh, Rc, C, Y, Y2, W/E, W2, G, B, O
T755	7D	5/1/1 NP	4*	2	•	•	•	7	•	•	•	•	•	•					3	5	Rh, Rc, C, Y, Y2, W/E, W2, G, B, O

Stages* = One less stage for conventional heat and cool.



T751



T755

The industry's best private label program.

rev. 2306



1-800-PRO1-559 (776-1559)

PRO
www.proliaq.com