

spec sheet

PRODUCT CODE: TDST



General Features

Dual Group super automatic two-step espresso maker with automated steam and foaming wand for milk drinks. This unit is typically operated for capacities upward of 48 lbs. per week. Designed for rugged commercial application and high performance during rush periods. Two 60,000 cycle piston seals require the Duo the least amount of intervention. The two independent stainless steel brewing chambers and software design replicate and consistently deliver infusion parameters found in barista controlled equipment. Adjustable and transferable settings via touch screen and USB.

Tango Unique Features

- 2 bean hoppers 3.75 lbs. each with low beans warning option
- Hopper stoppers for each hopper allows for easy removal of hoppers
- 2 precision grinders with 80 mm Mahlkonig burrs
- 1 Integrated SteamAir wand with auto milk foamer and programmable temperature control
- 48 programmable and customizable icon recipes through touch screeen display
- Adaptable for various coffee profiles and exceptional extraction quality obtained through full control of 9 infusion parameters: 2 grinders; 2 temperatures; tamping; 2 pre-infusion methods; weight of coffee; volume of water
- Temperature regulation for steam, coffee and group
- Independent steam and coffee boilers with abundant steam supply to eliminate recovery time
- 2 convenient telescopic dismountable double coffee spout
- 1 telescopic programmable hot water dispenser
- Large waste bin with overfill safeguard holds up to 120 cycles of used ground
- Day/Night Mode
- Drink counter
- Quick clean cycles every 90 drinks; complete group auto clean cycle every 24 hours
- Cup Warmer
- Stainless steel panels and steel framework
- Full sized rotary vane pump
- Cappuccino and Latte capable

TANGO S DUO	
Dimensions (W X D X H)	24" X 24" X 36"
Boiler Capacity - 2 boilers	6.5 Liters each – 6800 watts total
Power Requirements	208 V – 8700 W – 50 A – 1 Phase
Weight	235 lbs.
Shipping Weight	290 lbs.
Shipping Dimensions (W X D X H)	44" X 30" X 32"

Included:

- 100 cleaning tablets use 1 per day
- 1 tube of Superlube for cleaning cap
- Technician and operator control cards
- USB card for download and upload of settings
- Plumbing tubes for water (1/2"NPT) and drain line
- Adjustable LED lighting

