

Patented Self-Cleaning Condenser

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

D · ·	
Project	•
Project	

Model #: Item # :

Qty :

Available W/H :

Approval :

Horizontal Open Display Cases

Slim Line Glass Side Panel / Solid Side Panel

Model : TOM-50S(B) / TOM-50S-SP(-A) **NO PLUMBING REQUIRED**



____ FEATURES & BENEFITS =___ Maintenance-free, Self-Cleaning Condenser

(patented) Only at Turbo Air

The accumulation of dust in the condenser causes the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products in refrigerators. The self-cleaning condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

Hot gas condensate system Only Turbo Air models

Through Turbo Air's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but also prevents the overflow of condensate water.

- Modern design
- Optional solid side panels (SP & SP-A) available* to ensure durability with two interior standards (SB only) SP: Stainless steel interior for sanitary purposes

SP-A: Black coated interior with mirrored sides for maximized display effects

- Optional stainless steel front panel (SF) available*
- Ton display dwy assas (TOMD) sysilable (antispal)

Efficient refrigeration system

Turbo Air's refrigerators are designed with oversized and balanced environmentally friendly R-134A (CFC Free) refrigeration. These include large evaporators and condensers for faster cooling and balanced temperature throughout the cabinet.

- LED lighting interior
- Standard back-guard improves airflow
- 300 series stainless steel interior standard including back wall, shelves and deck pans
- Perforated interior back wall and top for improved air flow
- Foamed with polyurethane, high-density cell insulation (CFC free)
- Front air intake and rear air discharge

 Top display dry cases (TOMD) available (optional) 					c Contraction of the second se	Intertek
Model	CU./FT.	# of Bottom Shelves	HP	AMPS	Crated Weight (lbs.)	L x D x H (inches)
TOM-50S(B) TOM-50SB-SP(-A)	8.98	3	1/2	11	481	503/4 x 345/8 x 411/2

* For the 'Solid Side Panels (SP & SP-A) and Stainless Steel Front Panel (SF)' options, please allow 8-10 weeks lead time for shipping.

Horizontal Open Display Cases

Slim Line Glass Side Panel / Solid Side Panel

Model : TOM-50S(B) / TOM-50S-SP(-A)

ELECTRICAL DATA					
Voltage	115/60/1				
Plug Type	(i) NEMA 5-15P				
Full Load Amperes	11				
Compressor HP	1/2				
Refrigerant	R-134A				
DIMENSIONAL DATA					
Net Capacity (cu. ft.)	8.98				
Ext. Length Overall (in.)	503/4 (1289mm)				
Ext. Depth Overall (in.)	345/8 (880mm)				
Ext. Height Overall (in.)	411/2 (1054mm)				
Int. Length Overall (in.)	483/8 (1229mm)				
Int. Depth Overall (in.)	24 (610mm)				
Int. Height Overall (in.)	13 (330mm)				
Net Weight (lbs.)	370				
Gross Weight (lbs.)	481				
# of Bottom Shelves	3				
	481/4 x 111/4				
Shelf Size (L x D)(in.)	481/4 x 141/4				
	481/4 x 7				

Design and specifications subject to change without notice. Actual shipping weight may differ due to extra packing materials for product protection

• WARRANTY : 2 Year Parts and Labor Warranty Additional 3 Year Warranty on Compressor

- Simple plug-in installation
- Patented self-contained system, no plumbing required
- White and black color come standard
- 4" dia. casters available (optional)
- Night cover available (optional, white / black)
- Recommended operating conditions: TOM models are designed to operate in an environment where temperature & humidity do not exceed 75°F and 55% respectively. Units should not be installed near HVAC vents, fans or doorways that will disrupt the air curtain and compromise the function of the cabinet. Air curtain models will run most efficiently when completely loaded with product.

OPTIONAL ACCESSORIES :

- □ 4" caster, ½" diameter & 13 TPI: G8F6500101 (non-brake), G8F6500201 (w/ brake)
- Top display dry cases: TOMD-50-L (Low), TOMD-50-H (High)
- Night cover: NCT-50-W (White), NCT-50-B (Black)
 * Night cover option won't be able to apply on TOM-L/S models if TOMD dry case is already installed on top of the unit.
- □ Stainless steel front panel available: TOM-S-SF (extra lead time will apply, please call factory for more details to order)


















PLAN VIEW



SIDE VIEW



FRONT VIEW

■ Warranty : 800-381-7770 ■ AC : 888-900-1002

Turbo Air : 800-627-0032 **GK** : 800-500-3519