36", 42", & 48" TPI Industrial Belt Drive Portable Blowers





CORD WRAP INCLUDED WITH STANDARD MODEL

STANDARD MODEL

▲ WARNING: This product can expose you to chemicals including nickel which is known to the State of California to cause cancer, and chromium, which is known to the State of California to cause birth defects and/or reproductive harm. For more information go to www.P65Warnings.ca.gov.





Features

- Comes in sizes 36", 42", and 48"
- Rocker switch on 120V, Single Phase models
- SJT type 3 conductor, 12' long cord on 120V, Single Phase models / no cord on dual voltage models
- 4 paddle blade: 36" PBX / PBSX & HL have aluminum blade;
 42" & 48" PBX / PBSX have steel blade
- · Spiral, wire front and rear guards
- Corrosion and dent proof high density polyethylene housing
- 8" wheels (36" model), 10" wheels (42" & 48" models)
- Swivel model rotates 112.5° in 22½° increments and locks in place with a steel locking pin
- External junction boxes on dual voltage models allow units to be wired for either voltage without removing guards
- Hazardous location models have explosion proof motors, metal housings, and external junction boxes rated for Class I, Group D and Class II, Groups E, F, & G
- Meets OSHA standards
- 1 year limited warranty
- Made in U.S.A.

Motor Specifications

• 1-Speed

- Ball bearing
- Permanently lubricated

Standard Models

MOTOR LISTING	SIZE	MOTOR				CFM**	VELOCITY PROFILE	STANDARD MODEL			SWIVEL MODEL		
							CFM / Area	MFG	MFG	WT.	MFG	MFG	WT.
		TYPE	НР	RPM	AMPS		Sq Ft	CATALOG NUMBER	MODEL NUMBER	(LBS)	CATALOG NUMBER	MODEL NUMBER	(LBS)
	36"	120 V 1 PH ODP	1/2	500	8.0	6,900	14000 / 360	08211402	PBX 36-B	120	08213302	PBXS 36-B	145
c Ustro Us	42"		3/4	430	11.0	10,600	17500 / 420	08211502	PBX 42-B	135	08213402	PBXS 42-B	160
Intertek	48"		1	390	15.0	14,400	23500 / 550	08211602	PBX 48-B	155	08213502	PBXS 48-B	180
c LUSTED US Intertek	36"	240/480 V 3 PH ODP	1/2	500	2.3 / 1.1	6,900	14000 / 360	08508602	PB 36-B-3	127	08509202	PBS 36-B-3	152
	42"		3/4	430	3.3 / 1.5	10,600	17500 / 420	08508702	PB 42-B-3	143	08509302	PBS 42-B-3	168
	48"		1	390	3.4 / 1.7	14,400	23500 / 550	08508802	PB 48-B-3	164	08509402	PBS 48-B-3	189
	36"	120/240 V 1 PH EXP	1/2	500	7.8 / 3.9	6,900	14000 / 360	08508902	PB 36-B-HL*	135	08509502	PBS 36-B-HL	160
	42"		3/4	430	10.8 / 5.4	10,600	17500 / 420	08509002	PB 42-B-HL*	150	08509602	PBS 42-B-HL	175
	48"		1	390	13.2 / 6.6	14,400	23500 / 550	08509102	PB 48-B-HL*	173	08509702	PBS 48-B-HL	198

^{**}Measured 2 feet from face of fan *Models have no listing.