

TW Series



Features

- Single and double pole models
- Wire leads
- Tamper resistant
- Imported to TPI Corporation specifications

Load Rating

- 22 Amps resistive @ 120 VAC
- 18 Amps resistive @ 277 VAC

UPC#	MODEL	DESCRIPTION	TEMPERATURE SCALE
686334			
502009	TW145	SP, Beige with Leads	Tamper Resistant
502016	TW146	DP, Beige with Leads	Tamper Resistant
Master Carton: 25 Pcs, 12 lbs. (varies slightly by model), 16" x 14" x 5.5"			

Washdown Series



Features

- Single and double pole models
- Rain tight NEMA 4X rating
- Stainless steel hardware
- Coil capillary temperature sensor
- Made in U.S.A. with domestic and foreign components.

UPC#	MODEL	DESCRIPTION	TEMPERATURE SCALE
686334			
523424	TW155A	SP, Rain tight	40-110°F
523431	TW255A	DP, Rain tight	40-110°F
22 Amps @ 120/250/277 VAC, 5" x 5" x 3" Case			

Industrial Series



Features

- Coil capillary (CKT) models
- Bi-Metal models (KT)
- Rugged steel case
- SPST & SDPT models
- Imported to TPI Corporation specifications
- Hard wired models rated for 22A resistive @125-250 VAC
- Coded models rated for 13A resistive @125VAC

UPC#	MODEL	DESCRIPTION	RANGE	CONNECTIONS	SCALE
686334					
534048	CKTD110	SPDT Heat or Cool	40 - 110°F	Wire Leads	F
534086	KT110	SPST Heat Only	-10 - 100°F	Wire Leads	C & F
534109	KT121	SPST Heat Only	-10 - 100°F	6' Cord/Plug	C & F
534178	KTD110	SPDT Heat or Cool	-10 - 100°F	Wire Leads	C & F
534369	KTO110	SPST Cool Only	-10 - 100°F	Wire Leads	C & F
534215	KTO121	SPST Cool Only	-10 - 100°F	6' Cord/Plug	C & F
Master Carton: 13.75" x 14" x 9", Qty 9-12, 14lbs.-16lbs. depending on model					

LB Series - Bi-Metal In-Built Thermostats



LB110



LB210



Features

- Bi-Metal sensor
- HP Ratings: 3/4HP @ 125 VAC - 1.5HP @ 250-277 VAC
- 22 Amps resistive max

UPC# 686334	MODEL	DESCRIPTION	VOLTAGE	RANGE	CONNECTIONS
536134	LB110	SPST Heat Only	120-277 VAC	0 - 110°F	6" - 14 Gauge Leads
536202	LB210	DPST Heat Only			6" - 14 Gauge Leads
Master Carton: 16" x 14.5" x 6", Qty 25-50, 11lbs.-14lbs. depending on model.					