

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :	
Model #:	
Item #:	Qty:
Available W/H :	
Approval :	

# Back Bar

Underbar Equipment Super Deluxe Series

**Model: TBB-1SB-N6** 



## \_\_\_ FEATURES & BENEFITS =\_\_

#### ■ Hydrocarbon refrigerants (R-600a)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

#### ■ Forced air cooling system

Fast cooling and balanced temperature throughout the cabinet.

#### ■ Ergonomically designed doors

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience.

#### ■ High-density polyurethane insulation

The entire cabinet structure is foamed-in-place using high density, HCFC free polyurethane insulation.

## ■ Stainless steel countertop and interior

The exterior of the cabinet is constructed with heavy gauge reinforced stainless steel countertop and wear-resistant black vinyl coated galvanized steel. The interior is painted galvanized steel with reinforced stainless steel floor. Turbo Air Back Bar model guarantees the utmost in cleanliness and long product life. It also adds a touch of style to the most refined setting.

- LED interior lighting
- Adjustable, heavy duty, PE (polyethylene) coated wire shelves
- Refrigerator holds 33°F ~ 38°F for the best in beverage preservation











Model	Swing Door	CU./FT.	1/2 Barrels	#of Shelves	НР	AMPS	Crated Weight (lbs.)	L x D*x H† (inches)
TBB-1SB-N6	1	7.76	1	2	1/8	1.3	235	235/8 x 321/8 x 373/4

(unit: inch)

## **Model: TBB-1SB-N6**

ELECTRICAL DATA					
Voltage		115/60/1			
Plug Type		① NEMA 5-15P			
Full Load	Amperes	1.3			
Compress	or HP	1/8			
Refrigerar	nt	R-600a			
Cord Leng	gth (ft.)	8.5			
Lamp (W)		6.5			
DIMENSIONAL DATA					
Capacity	1/2 Barrels	1			
Сараспу	Cubic Feet	7.76			
Ext. Lengt	h Overall (in.)	23 <sub>5/8</sub> (599mm)			
Ext. Depth	o Overall (in.)*	321/8 (816mm)			
Ext. Heigh	nt Overall (in.)†	37 <sub>3/4</sub> (875mm)			
Net Weigh	nt (lbs.)	190			
Gross We	ight (lbs.)	235			
# of Swing	Door	1			
# of Shelv	es	2			
Shelf size	(L x D) (in.)	181/2 x 191/2			
# of Caste	ers	4EA			

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

■ WARRANTY: 3 Year Parts and Labor Warranty
Additional 4 Year Warranty on Compressor

### STANDARD FEATURES


- · Anti-corrosion coated evaporator
- · Self-contained system
- 4" dia. swivel casters standard
- · Door locks standard

#### ■ OPTIONAL ACCESSORIES:


☐ Additional PE coated wire shelf: P0178D0100

☐ 6" adjustable stainless steel leg: P0121P0100


## **PLAN VIEW**



**TOP VIEW** 



**FRONT VIEW** 



Ver.20200706











■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519

■ Warranty: 800-381-7770 ■ AC: 888-900-1002











<sup>\*</sup> Depth does not include 2" for rear spacers. † Height does not include 5" for caster height.