Technical Information



M-iClean UM

Type: M2

Execution for: USA

Dishwashing machine

208V/230V/60Hz/3Ph

Fresh water line: Soft cold water 1-3 grains per U.S. gal

ComfortAir (heat recovery)



Sample illustration

_				
-1Δ	chr	NICO	l data	
16	CHI	IICa	ı uata	

Cycles/hr (theoretical)	37 / 24 / 17 racks/hr	
Program cycle	95 / 150 / 210 s, plus vapour treatment 120 s	
Dishrack dimension	1' 7 5/8" x 1' 7 5/8" / 500 x 500 mm	
Entry height	315 (1'-0 3/8") mm	
Dimensions (W x H x D)	1' 11 5/8" x 2' 4 6/8" x 1' 11 5/8" / 600 x 730 x 600 mm	
Electrical feeding cable	208V/230V/60Hz/3Ph	
-	Total connected load: 7.7 kW / 9.5 kW	
	max. rated current: 31.1 A / 36.4 A	
Features and options	Control system MIKE CPU4	
	Bluetooth interface for wireless communication	
	Leakage detector	
	Boiler safety device	
	Automatic self-cleaning when tank is drained	
	ComfortAir (heat recovery)	
Fresh water backflow prevention	Air gap 'AB' in accordance with EN 1717 with booster pump	
Fresh water supply	Flow pressure 8.7 psig - 72.5 psig / 0.6 bar - 5.0 bar	
	Max. incoming water temperature 68 °F / 20 °C	
Water consumption	0.79 U.S.gals/cycle / 3.0 liters/cycle	
Booster heater	Contents: 2.1 U.S.gals / 7.9 I	
	Heater: 4.50 kW	
	Temperature: 181 °F / 83 °C	
Wash tank	Filling: 2.9 U.S.gals / 11.0 I	
	Heater: 4.00 kW	
	Temperature: 163 °F / 73 °C	
Wash pump, with frequency converter	Performance: 0.50 kW	
Rinse aid pump	Peripump (24 V) with time control	
Detergent pump	Peripump (24 V) with time control,	
	empty indicator	

M-iClean Page 1 / 2 MP000023510.2.2 M-iPlan 1/28/2020

Technical Information



Cladding: SS Grade SAE 304 / Germany 1.4301	
Wash tank: SS Grade SAE 304 / Germany 1.4301 (mirror finish)	
Booster heater: SS Grade SAE 316Ti / Germany 1.4571	
for 10 program cycles/hr	
total: 0.8 kW	
perceptible: 0.65 kW	
latent: 0.15 kW	
0.22 lbs/hr / 0.1 kg/hr	
60 dB	
142.7 lbs / 64.7 kg /	
219.8 lbs / 99.7 kg (standard packaging)	
2' 4 6/8" x 6' 10 5/8" x 2' 4 6/8" / 730 x 2100 x 730 mm (standard packaging)	

The component data is referring to 230 V, unless otherwise indicated. Machines are NSF listed under the name M_iClean.

M-iClean Page 2 / 2 MP000023510.2.2 M-iPlan 1/28/2020