TECHNICAL DATASHEET

October 2024



W6A UL Gas coffee roaster

One roaster, infinite potential

Quality and functionality should always go together, and this reflects in our products. **The W6 series is handmade with high-quality materials.** We designed this roaster with two different fans. This way you can roast and cool simultaneously while also increasing the production capacity up to 24 kg. per hour.

Ultimate roasting control

Take roasting into your own hands with the W6 series. With our own developed software, it is possible to record and replay a roast with the related settings, enabling you to maintain the same quality levels for multiple batches.

Why a Giesen W6 series roaster?

Gregory Koifman, founder of Ethica coffee roasters explains; "I am delighted with the roaster. It feels like roasting never was more smooth, especially with such easy maintenance. It was essential for me to find a roaster that would fit into the interior of the coffee shop. Giesen produces high-tech machines with perfect, thought-through designs."







Full control

We don't want to limit your coffee roasting options. That is why options such as airflow, drum speed and power control are **included as standard.** Take advantage of the freedom a Giesen roaster gives you!

Support and service

When it comes to service and support, our team is unparalleled. Our knowledgeable experts and user-friendly tools enable us to offer exceptional customer service, guaranteeing complete satisfaction with our products.

Dutch design

Our goal is to create roasters that bring a smile to your face, embodying your personality and filling you with pride. With a vast array of design options, you have the ability to **fully customize** your roaster to your exact preferences.





Ranges

Underpressure range 80 - 150 Pa (min. - max.)

Default value: 110 Pa

Drum range 52 - 74 RPM (min. - max.)

Hz and RPM can be selected Default value: 67 RPM

Temp. setpoint range 212 - 482 °F (min. - max.)

°C and °F can be selected Default value: 392 °F

Electrical specifications

Supply voltage 120 / 240 V AC 2L+N+PE

3-phase system, supply frequency 60 Hz

External fusing 1 x 5A

Max. electrical power 1,7 kW

Certifications



Chimney specifications

Chimney diameter Ø 150 mm

General specifications

Measurements 1427 (L) x 723 (W) x 1705 (H)

Weight 485 kg roaster only

Minimum batch size 3 kg

Maximum batch size 6 kg

Sound level 70 dB (A)

Gas specifications

Gas connection G 3/8" (M)

Max. gas consumption

Gas inlet pressure

Additions

Giesen Profiler

Destoner


Green Coffee Conveyor


External cyclone

SFE filter

Support router

CEC Catalytic Emission Cleaner







Get adequate information or a personalized quote by scanning the QR code. It's quick, easy, and convenient - the perfect way to get the information you need in no time!

