

## DESCRIPTION

WashBasic LLL has been designed for applications where a cost-effective system, with 2/3 product solutions, is required. Due to its reduced dimensions, the system is ideal for installation in narrow spaces.

## FEATURES

- 2 or 3 pumps, independently programmable
- Can be set in Sequence mode to ignore the triggers of the previous washing phases
- Motor Block alarm to prevent motor failure in case of high pressure at injection point or clogging of delivery tubing
- 3 independent triggers able to drive up to 3 pumps each one
- Triggers accepting signals from 24 to 230 Vac 50/60Hz
- Calibration function for a perfect dosing



## TECHNICAL SPECIFICATIONS

<b>Power supply</b>	100 ÷ 230 Vac @ 50/60 Hz (24 Vac available upon request)
<b>Power consumption</b>	40 W
<b>Dosing quantity</b>	from 1 to 500 gr
<b>Delay time</b>	from 1 to 15 minutes
<b>Level control input</b>	3 inputs, with acoustic alarm and relay for remote alarm
<b>Class of protection</b>	IP 55 Plastic enclosure
<b>System dimensions (L x H x D)</b>	285 x 230 x 115 mm (11.2" x 9.1" x 4.5")
<b>Max Operating Temperature</b>	50°C

## DIMENSIONS

