



## Snapshot

IFQ Series water treatment systems reduce sediment down to 1/2 micron and reduce chlorine, taste and odor at a flow rate of up to 3.0. The systems include IsoNet®, which delivers consistent protection against the precipitation and accumulation of scale and provides a protective barrier to help guard against corrosion.

## Features and Benefits



- Reduces maintenance frequency and cost, and extends equipment life.
- Improves equipment operating efficiency
- Incorporates IsoNet - patented scale-inhibiting technology.
- Gradient-density depth filtration reduces dirt, rust and other debris as small as 1/2 micron to ensure clean, clear ice and protect solenoids, valves and other fittings against wear and plugging.
- High-capacity activated carbon filtration reduces taste and odor and protects equipment against corrosive chlorine.
- 1/4 turn QT "Quick-Twist" cartridge makes changing the filter quick, easy and sanitary.
- Wall-mount bracket and full-flow inlet shut-off valve make installation simple.
- NSF certified under Standard 42


## Installation Tips


- Feed-water connection to system should be COLD only.
- Do not exceed system specifications for temperature and pressure.
- Allow 3" clearance below system for cartridge removal and replacement.
- Connect filtered water line to ice connections only. Do not use for condenser water.
- No activation procedure or flushing is required for system to perform as specified.

IFQ SERIES FILTER SYSTEM						
Model Number	Description	Service Flow Rate Max. gpm (lpm)	Pressure Max. Psi (bar)	Inlet Water Temp Range °F (°C)	Micron Rating	Approx. Shipping Weight lbs (kg)
IFQ1	Single Filter	1.5 (5.68)	10 - 125 (0.7 - 8.6)	100 (38)	.5	3 (1.3)
IFQ1-XL	Single Filter	2.25 (8.5)				5 (2.3)
IFQ2	Dual Filter	3.0 (11.4)				7 (3.2)
IFQ2-XL	Dual Filter	4.5 (17)				9 (4.1)

SINGLE INLINE FILTER CARTRIDGES						
Model Number	Description	Service Flow Rate Max. gpm (lpm)	Pressure Max. Psi (bar)	Inlet Water Temp Range °F (°C)	Micron Rating	Approx. Shipping Weight lbs (kg)
IFI4C	Single Inline Cartridge 1/4" (6.35mm) compression	1.0 (3.79)	10 - 100 (.07 - 6.9)	35 - 100 (2 - 38)	10	2 (1)
IFI8C	Single Inline Cartridge 3/8" (9.53mm) compression					

**IFQ Series  
Filter Systems**
**Single Inline  
Filter**
**Replacement  
Filter Cartridges**

**IFQ1**  
 15" H x 6" W x 4" D  
 (381 mm x 152 mm x 102 mm)

**IFQ2**  
 16" H x 10" W x 7.125" D  
 (406 mm x 254 mm x 102 mm)

**IFQ1-XL**  
 21" H x 6" W x 4" D  
 (533 mm x 152 mm x 102 mm)

**IFQ2-XL**  
 23.21" H x 13" W x 4.65" D  
 (590 mm x 330 mm x 118 mm)

**IF14C / IF18C**  
 11.75" x 2.75"  
 (297 mm x 57 mm)

**IOMQ**  
 12.75" x 4"  
 (324 mm x 102 mm)

**IOMQ-XL**  
 17.49" x 3.9"  
 (444 mm x 99 mm)

**All filter systems include:**

Filter cartridge with FDA approved scale inhibitor, inlet shut-off valve, gauge and quick-connect fittings.

\*IOMQ replacement cartridges for use with IFQ1 &amp; IFQ2 manifold filter systems. IOMQ-1XL replacement cartridge for use with IFQ1-XL manifold filter system.

WATER FILTERS						
		IF14C / IF18C	IFQ1	IFQ1-XL	IFQ2	IFQ2-XL
CUBE ICE	ICEU070	X	X			
	ICEU150 - ICEU220	X	X			
	ICEU300			X		
	CIM0320 - CIM0430		X			
	CIM0520 - CIM0630			X		
	CIM0830 - CIM1130				X	
CIM1440 - CIM2046					X	
FLAKE ICE	MFIO500	X	X			
	MFIO800 - MFII256			X		
	MFII506				X	
	MFII2306					X
PEARL ICE	GEMU090	X				
	GEMO450 - GEMO650		X			
	GEMO950			X		
	GEM1306				X	
	GEM2006					X

**Extended Warranty Program**

- Buy a new Ice-O-Matic Water Filter System with a new CIM Series™ Cube ice maker, replace the filter cartridge every 6 months, and Ice-O-Matic will extend the limited cuber evaporator warranty to 7 years parts and labor (U.S. and Canada only).
- New ice maker and filter must be installed at the same time.
- Ice maker and water filter must be registered with Ice-O-Matic within 10 days of installation. Register ice maker and filter at [www.iceomatic.com](http://www.iceomatic.com).
- Water filters must be changed every 180 days (6 months), at a minimum. All changes must be registered with Ice-O-Matic and include the water filter's model and serial numbers. Register water filter changes at [www.iceomatic.com](http://www.iceomatic.com).
- Program is available with all Ice-O-Matic IFQ1, IFQ1-XL, IFQ2, IFQ2-XL, IF14C or IF18C water filter systems.
- Replacement filter must be Ice-O-Matic models.