



Corrugated Copper Water Heater Connectors (EFWC-034C-Series)

Innovative copper water heater connectors with optimized helical corrugation provide maximum flow and flexibility. Helical flow reduces mineral deposit and reliable di-electric sleeves prevent galvanic corrosion.

FEATURES

- Maximum flow with engineered and optimized corrugation design
- Built-in Di-electric sleeve to prevent possible galvanic corrosion
- Lead-Free certified
- SWEAT connection option for copper tubing
- Chrome-plated brass nut and high-quality EPDM washer
- 100% Leak tested

MATERIALS

Tubing	Copper
Nut	Chrome-Plated Brass 3771
Gasket	High-Quality EPDM

SPECIFICATIONS

Operation Temperature	-40°F to 180°F (-42°C to 82°C)
Intermittent Impulse Pressure	Up to 180 psig
Operation Pressure	20 to 125 psi (8.6 bar)

DESIGN CERTIFICATIONS AND APPROVALS

- ASME A 112.18.6-2009 / CSA B 125.6-2009
- IAPMO / UPC Certified
- NSF 61 Compliant
- NSF 372 Compliant : Lead-Free



Job Name :

Engineer / Architect :

Job Location :

Wholesaler :

Submittal Date :

Contractor :





WEST OFFICE
(888) 577-8999
EAST OFFICE
(855) 388-2600

Easyflex reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modification on Easyflex products previously or subsequently sold.

Corrugated Copper Water Heater Connectors

(EFWC-034C-Series)

Image	Tube ID	Part #	Description		Qty / Box
			Hose & Fittings	Length	
	3/4"	EFWC-034C-1010-12	WC Copper Flex 3/4" FIP x 3/4" FIP	12"	25
		EFWC-034C-1010-15		15"	25
		EFWC-034C-1010-18		18"	25
		EFWC-034C-1010-24		24"	25
		EFWC-034C-1060-12	WC Copper Flex 3/4" FIP x 3/4" Sweat	12"	25
		EFWC-034C-1060-15		15"	25
		EFWC-034C-1060-18		18"	25
		EFWC-034C-1060-24		24"	25