

Waterloo Deck-Mounted Matte Black Hands-Free Dual-Sensor Faucet with Foam Soap Dispenser

#750EFDMSDBK

Item#: 750EFDMSDBK	Qty:
Project:	
Approval:	Date:





Features

- Dual sensor foam soap dispenser and water faucet, 1.2 GPM flow rate
- Deck-mounted single hole base with stainless steel supply line to connect module to faucet
- 9/16"-24 female connector fittings
- Solid brass construction with matte black finish for long life
- Includes AC adapter and control module

Certifications





ADA Compliant



3/8" Water Connection




CSA, US and Canada

Technical Data	
Spout Length	6 5/16 Inches
Faucet Width	2 3/4 Inches
Faucet Height	5 7/8 Inches
Adjustable Sensor Range	1 Inches 6 Inches
Capacity	1500 mL
Color	Black
Dispenser Style	Deck Mount
Dispenser Type	Automatic
Faucet Centers	Single

Technical Data	
Features	ASME A112.18.1-2018 / CSA B125.1-18 Massachusetts Accepted Plumbing Product NSF/ANSI 372 NSF/ANSI 61
Finish	Matte Black
Flow Rate	1.2 GPM
Included	Flex Inlets
Material	Brass
Mounting Holes Required	1 Mounting Hole
Mounting Style	Deck Mounted
Power Type	AC Adapter
Spout Clearance	3 1/8 Inches
Spout Type	Cast
Style	Foaming
Temperature Rating	41 - 158 Degrees F
Туре	Touchless Faucets
Water Inlet Size	3/8 Inches

Plan View



Notes & Details

This Waterloo matte black dual-sensor faucet is the perfect solution when you need a dependable water fixture for your facility's restrooms and hand-washing areas! It features a dual sensor foam soap dispenser and water faucet on a single hole base, with a matte black finish that provides a contemporary and refined look wherever it's installed. The sensor is also concealed so as to be more aesthetically pleasing than a traditional base-mounted sensor. Made from solid brass with a matte black finish, this dual faucet provides a polished look and superior durability.

This faucet is equipped with an infrared proximity sensor with an adjustable range of 1"-6" and a rapid 0.2-second water response time. It also features a 1500 mL soap reservoir that dispenses soap in just 2 seconds. Foaming soap (sold separately) is required for use. To avoid the risk of clogging, the soap dispenser will automatically dispense soap once every 12 hours when not in use. Because a sensor activates both the soap and water flow, it has several advantages over a traditional handle-style faucet. It is hands-free, which reduces the opportunity for germs to length, and it also prevents the faucet from running when it's not needed, which helps to cut down on your water bill.

The UL certified AC adapter with a Level VI efficiency rating is included to provide power for the faucet's control module, which installs below the countertop and connects to the faucet with a flexible stainless steel supply line. A mixing valve also allows you to easily set the output temperature to the desired level between 41 and 158 degrees Fahrenheit. This prevents burned hands from water that is too hot, while still ensuring that the water is warm enough for users to effectively wash their hands. 9/16"-24 female connector fittings connect the mixing valve to your building's water lines.

Waterloo sensor faucets provide the industry-leading quality you expect. With a heavy brass faucet body and certifications from a wide range of national and local regulatory agencies, you can install this model with confidence. And to give you total peace of mind, it comes with a 3-year replacement warranty.

⚠ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov .