




Waterloo Wall-Mounted Faucet with 8" Centers and 15" Double-Jointed Swing Spout

#750FW815DJ

Item #: 750FW815DJ Qty: _____
 Project: _____
 Approval: _____ Date: _____



Features

- 15" double-jointed swing spout with 2 GPM aerator
- 8" adjustable centers, 1/2" NPT inlets
- Temperature rating 40 - 180 degrees Fahrenheit
- Heavy-duty chrome-plated brass construction
- Leak-resistant 1/4 turn ceramic cartridges with check valves

Certifications



CSA, US and Canada



NSF Certified




1/2" Water Connection

Technical Data

| | |
|----------------|--------------|
| Spout Length | 15 Inches |
| Faucet Height | 7 3/4 Inches |
| Cartridge Type | Ceramic |
| Faucet Centers | 8 Inches |
| Finish | Chrome |
| Flow Rate | 2 GPM |
| Handle Type | Lever |
| Material | Brass |
| Mounting Style | Wall Mounted |
| Mounting Type | Adjustable |

| Technical Data | |
|-----------------------|--------------------------|
| Rough In | 8 Inches |
| Spout Clearance | 5.440000057220459 Inches |
| Spout Connection Size | 1"-20 UNEF |
| Spout Type | Double Jointed |
| Temperature Rating | 40 - 180 Degrees F |
| Thread Type | NPT |
| Type | Faucets |
| Water Inlet Size | 1/2 Inches |

Plan View



Notes & Details

This Waterloo wall-mounted faucet is the perfect solution when you need a dependable water fixture in your facility! Waterloo faucets provide the industry-leading quality you expect. With heavy chrome-plated brass faucet bodies, ceramic cartridges engineered for durability, and certifications from a wide range of national and local regulatory agencies, you can install this model with confidence. And to give you total peace of mind, it comes with a 3-year replacement warranty.

This faucet features a 15" long double-jointed swing spout that gives greater range of motion than a standard swing nozzle, with the added benefit of allowing you to fold it out of the way to accommodate large, bulky items. A 2 GPM aerator provides a consistent flow rate and minimal splashing. It boasts a set of 8" adjustable centers, while the wall-mounted design is easy to install with 1/2" NPT inlets.

This faucet uses ceramic cartridges, which provide a much lower fail rate than the compression cartridges widely used in the industry. In this design, 2 ceramic discs fit together to create a watertight seal when closed. This removes the need for a rubber seat washer, which is one of the most frequently replaced parts on a faucet. The sturdy lever handle design makes it easy to turn the water flow off and on.

⚠ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.