


- 44" hose with 1.15 GPM spray valve
- Deck-mounted design with single base, 1/2" NPT inlets, and 20" water lines included
- Quarter-turn ceramic cartridges and check valves for high performance
- Heavy-duty faucet base and spray valve with chrome-plated brass construction
- Includes 18" riser and 6" wall bracket

Certifications





1/2" Water Connection

Waterloo 1.15 GPM Deck-Mounted Pre-Rinse Faucet with Single Base

#750PRDX

Item #: 7	50PRDX	Qty:	
Project:			
Approval:		Date:	






Technical Data	
Hose Length	44 Inches
Faucet Height	35 Inches
Rough-In Diameter	1 1/8 Inches
Add-On Faucet	None
Cartridge Type	Ceramic
Faucet Centers	Single
Features	ASME A112.18.1-2018 / CSA B125.1-18 NSF Listed NSF/ANSI 372 NSF/ANSI 61

Technical Data	
Finish	Chrome
Handle Type	Lever
Material	Brass
Mounting Style	Deck Mounted
Mounting Type	Adjustable
Pre Rinse Unit Type	Hose and Spring
Spray Valve Flow Rate	1.15 GPM
Temperature Rating	180 Degrees F
Water Inlet Size	1/2 Inches

Plan View

750PRDX



Notes & Details

This Waterloo deck-mounted pre-rinse faucet is perfect for rinsing excess food and sauces off of your dishes prior to running them through your commercial dish machine. A quality pre-rinse unit is vital to any dishroom, removing the heaviest soil deposits so that dishes come out clean and ready to use. Waterloo products provide the industry-leading quality you expect. With heavy chrome-plated brass faucet bodies, ceramic cartridges engineered for durability, and certifications from a wide range of national and local regulatory agencies, you can install Waterloo products with confidence.

A 44" long flexible hose gives you plenty of reach to deliver water where you need it, letting you handle glassware and dinnerware, or bulky items like pots and pans. The spring has a compressed bottom to provide greater durability and help it retain its shape. The spray valve delivers a flow rate of 1.15 GPM, giving you the power needed to blast away food debris while being easy on your water bill. The heavy-duty valve body is designed with a comfort-grip handle and uses metal components for maximum durability and leak protection.

This faucet uses ceramic cartridges, which provide a much lower fail rate than the compression cartridges widely used in the industry. In this design, 2 ceramic discs fit together to create a watertight seal when closed, removing the need for a rubber seat washer, which is one of the most frequently replaced parts on a faucet. This is a deck-mounted faucet, and it comes with a single base that makes installation easy. The 1/2" NPT inlet connections, and a set of 20" flex hoses make it easy to connect it to your facility's water lines. This pre-rinse unit comes with an 18" riser and a 6" wall bracket to help secure the unit to the wall for added stability.

▲ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov .