

Features

- 23" hose, 0.65 GPM low flow spray valve
- Wall-mounted design with 8" adjustable centers, 1/2" NPT inlets
- 1/4 turn ceramic cartridges for long life and leak-protection, check valves prevent backflow
- Heavy-duty faucet base and spray valve, chrome-plated brass construction
- 6" add-on faucet (2 GPM), 10" riser, low height for heightrestricted areas

Certifications



SF Listed

1/2" Water Connection

Waterloo 0.65 GPM Low Profile Wall-Mounted Pre-Rinse Faucet with 8" Centers and 6" Add-on Faucet

#750PRWL86LF

| Item#: 750PRWL86LF | Qty: |
|--------------------|-------|
| Project: | |
| Approval: | Date: |
| | |






| Technical Data | |
|------------------|---------------|
| Hose Length | 23 Inches |
| Faucet Height | 20 1/2 Inches |
| Add-On Faucet | 6 Inches |
| Add-on Flow Rate | 2 GPM |
| Add-On Type | Swing |
| Cartridge Type | Ceramic |
| Faucet Centers | 8 Inches |
| Finish | Chrome |
| Handle Type | Lever |
| Material | Brass |

| Technical Data | |
|-----------------------|--|
| Features | ASME A112.18.1-2018 / CSA B125.1-18 California AB100 Compliant NSF/ANSI 372 NSF/ANSI 61 |
| Mounting Style | Wall Mounted |
| Mounting Type | Adjustable |
| Pre Rinse Unit Type | Mini Pre-Rinse Faucets |
| Spray Valve Flow Rate | 0.65 GPM |
| Temperature Rating | 180 Degrees F |
| Thread Size | 55/64"-27 UNS |
| Water Inlet Size | 1/2 Inches |

Plan View



This Waterloo low profile wall-mounted pre-rinse faucet is perfect for rinsing excess food and sauces off of your dishes prior to running them through your commercial dish machine, and its reduced height makes it a great fit for commercial kitchens where space is at a premium. A quality pre-rinse unit is vital to any dishroom, removing the heaviest soil deposits so that dishes come out clean and ready to use. Waterloo products provide the industry-leading quality you expect. With heavy chrome-plated brass faucet bodies, ceramic cartridges engineered for durability, and certifications from a wide range of national and local regulatory agencies, you can install Waterloo products with confidence. And to give you total peace of mind, this model comes with a 3-year replacement warranty.

A 23" long flexible hose gives you plenty of reach to deliver water where you need it, letting you handle glassware and dinnerware, or bulky items like pots and pans. The spring has a compressed bottom to provide greater durability and help it retain its shape. The spray valve delivers a flow rate of 0.65 GPM, giving you the power needed to blast away food debris while keeping your water bill low. The heavy-duty valve body is designed with a comfort-grip handle and uses metal components for maximum durability and leak protection. This prerinse unit also comes with a 6" add-on faucet, for times when you need a normal faucet instead of a spray valve. It is perfect for filling up sink compartments to complete your warewashing tasks. It's also great for mixing up cleaning solutions in sanitation pails.

This faucet uses ceramic cartridges, which provide a much lower fail rate than the compression cartridges widely used in the industry. In this design, 2 ceramic discs fit together to create a watertight seal when closed. This removes the need for a rubber seat washer, which is one of the most frequently replaced parts on a faucet. This is a wall-mounted faucet, and it comes with 8" centers that make installation easy. A set of 1/2" NPT inlets make it easy to connect it to your facility's water lines. Great for height-restricted installations, this low-profile pre-rinse unit comes with a 10" riser.

A WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.