	OPEN HEAD DRUM LI	FTER	INEL PACEMENT LAKES FIST			
			ITEM	PART NO. DESCRIPTION	QTY.	
	 For use with standard 3/16" chime. 	steel or poly drums with at least a	1	055828 WELDMENT: LIFTER	3	
	 Lifting arms are sdjust 	able to work with most 55 or 30	2	101136 PIN	3	
	gallon drums. • Three-point contact of	the lifting arms prevents or	3	101143 PIN: HAIR	3	
	minimizes deformation secure lifting.	the lifting arms prevents or of the drum and provides more	4	100051 WASHER	3	
	Secure inting. Also works on closed h	nead drums.	'	TOUGHT WHOME		
PRINT ISSUED	P/N 240038 Model OHDL-3 Capacity 1,000 lbs Weight 18 lbs Boxed YES PIVOT STOP PIVOT HOLE B (30 GALLON DRUM PIVOT HOLE A (55 GALLON DRUM POSITION)	POSITION) ITEM 1 IN 55 GALLO DRUM POSITION PIVOT HOLE A	IN ALL PARTICULARS	ITEM 1 IN 30 GALI DRUM POSITION PIVOT HOLE B S VESCO NOUSTRAL PRODUCTS INC. PROPERTY. ALL RIGHTS OF DESIGN, INVENTION OR L WESCO INDUSTRIAL PRODUCT	OOK ON SE OF ARE RESERVED. S INC.	
PKINI ISSUED			Ĭ ∏	NORTH WALES PENNA. 19		
		ا ا	UPDATED ECN & DATE REVISIONS	UUDF-2	04-17-08	
JUNE 17, 2009			ATE SATE	(DRUM LIFTERS SERIES) CHECKED: TOLERANCE UNLESS OTHERWISE SPECIFIED APP. ENGR.		
WESCO MANUFACTURING			g	FRACTION 3 PLACE DECIMAL 2 PLACE DECIMAL SCALE:	" = 1"	
ENGINEERING DEPARTMENT			الا	± 1/64 ± .005 ± .01 ANGULAR ± 1-1/2 SHEET 1 OF 1 C - 24(0038 ≱ C	

OPEN HEAD DRUM LIFTER

REPLACEMENT PARTS LIST

C−240038 ⊋ C

240038

WESCO MANUFACTURING ENGINEERING DEPARTMENT