

Project:	AIA#
ltem:	
Location:	SIS#
Approved:	

WORKTOP REFRIGERATOR

WTR27AHC Solid Door With Flat Top Hydrocarbon Series

MODEL: WTR27AHC-FLT



*Note: Shown with optional full electronic control

7 Year Parts/Labor Warranty7 Year Compressor Warranty

CABINET CONSTRUCTION

- Stainless steel front, sides, door and grille (galvanized back & bottom)
- · Interior liner is made of corrosion resistant aluminum
- · Stainless steel top for added durability
- Flat top
- Mechanical control
- · Interior thermometer is standard
- Self-closing door with 120° stay-open feature, on cartridge style hinges
- Magnetic gasket attached to each door for positive seal
- 6" Casters, two (2) with brakes standard
- Two (2) epoxy-coated steel wire shelves
- Field-reversible door (hinge kit not included)

OPTIONS & ACCESSORIES

- Stainless steel back
- Stainless steel interior
- 16 Gauge stainless steel top
- Full electronic control*
- Additional shelves
- Shelf clips
- · Glass door option
- Right or left hinged door
- Locks (solid doors only)
- · Wire shelf divider
- Cutting board
- 3" Casters
- 6" Legs (stainless steel, black or seismic/flange)
- · Low profile casters
- Roller kit
- Remote option** (see note on back on page)

REFRIGERATION SYSTEM

- Uses environmentally friendly, energy efficient R290 refrigerant, and meets all regulatory requirements for CARB, SNAP, DOE & more
- Adaptive defrost
- Epoxy coated evaporator coil
- Refrigerators capable of maintaining product temperature between 36°F and 38°F





3779 Champion Blvd., Winston-Salem, NC 27105 1-888-845-9800 Fax: 1-336-245-6453 Beverage-Air.com Sales@bevair.com




MODEL	WTR27AHC-FLT	
EXTERNAL DIMENSIONAL DATA		
Width Overall	27"	
Depth Overall with Handle & Bumper	32 ½"	
Height Overall with 6" Casters	35 ½"	
Number of Doors	1	
Depth with Door Open 90°	55 %"	
Door Opening	22 %" x 21 %"	
INTERNAL DIMENSIONAL DATA		
NET Capacity (cubic ft.)	6.13	
Internal Width Overall (in)	23"	
Internal Depth Overall (in)	18 ½"	
Internal Height Overall (in)	23"	
Number of Shelves	2	
ELECTRICAL DATA		
Full Load Amperes	2.0	
Voltage	115/60/1	
Nema Plug (8' cord)	5-15P	
REFRIGERATION DATA		
Horsepower	1/6	
Capacity (BTU/Hr)	1110	
Heat Rejection (BTU/Hr)	1665	
Charge (lbs/grams/ounces)	0.1323 / 60 / 2.12	
SHIPPING DATA		
Gross Weight - Crated	184 lbs	
Height - Crated	36"	
Width - Crated	30"	
Depth - Crated	32"	

**NOTE: Remote units are field wired and come with 6" legs. Refrigerant must be specified at time of order.

We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM).

Worktop Refrigerator Model: WTR27AHC-FLT



ELECTRICAL CONNECTION



Unit pre-wired at factory 115/60/1 and include 8 and plug set. and include 8' long cord



