

Project:	AIA#
Item:	
Location:	SIS#
Approved:	

WORKTOP REFRIGERATOR

MODEL: WTRD48AHC-4-FIP

WTRD48AHC Worktop With Drawers & Foamed-In Place Backsplash Hydrocarbon Series

7 Year Parts/Labor Warranty 7 Year Compressor Warranty



CABINET CONSTRUCTION

- Stainless steel front, sides, drawers and grille (galvanized back & bottom)
- Interior liner is made of corrosion resistant aluminum
- · Stainless steel worktop for added durability
- Foamed-in place backsplash
- Full electronic control
- Interior thermometer is standard
- Snap-in drawer gaskets
- Upper and lower pull-out drawers accommodate 6" deep pans
- Stainless steel drawer frames supported on telescoping drawer slides
- Drawer slides include locking mechanism that prevents drawer from being inadvertently pulled off cabinet
- 6" Casters, (2) with brakes standard

OPTIONS & ACCESSORIES

- Stainless steel back
- Stainless steel interior
- 16 Gauge stainless steel top
- · Cutting board
- 3" Casters
- 6" Legs (stainless steel, black or seismic/flange)
- Low profile casters
- Roller kit
- Remote option* (see note on back on page)

REFRIGERATION SYSTEM

- Uses environmentally friendly, energy efficient R290 refrigerant, and meets all regulatory requirements for CARB, SNAP, DOE & more
- Adaptive defrost
- Epoxy coated evaporator coil
- Refrigerators capable of maintaining product temperature between 36°F and 38°F






3779 Champion Blvd., Winston-Salem, NC 27105 1-888-845-9800 Fax: 1-336-245-6453 Beverage-Air.com Sales@bevair.com




MODEL	WTRD48AHC-4-FIP	
EXTERNAL DIMENSIONAL DATA		
Width Overall	48"	
Depth Overall with Handle & Bumper	32"	
Height Overall with 6" Casters	39 %"	
Number of Drawers	4	
Depth with Drawer Extended	48"	
Drawer Openings	(4) 19 %" x 9 ¾"	
INTERNAL DIMENSIONAL DATA		
NET Capacity (cubic ft.)	11.82	
Internal Width Overall (in)	44"	
Internal Depth Overall (in)	15 ¾"	
Internal Height Overall (in)	23"	
ELECTRICAL DATA		
Full Load Amperes	2.2	
Voltage	115/60/1	
Nema Plug (8' cord)	5-15P	
REFRIGERATION DATA		
Horsepower	1/6	
Capacity (BTU/Hr)	1094	
Heat Rejection (BTU/Hr)	1641	
Charge (lbs/grams/ounces)	0.2425 / 110 / 3.9	
SHIPPING DATA		
Gross Weight - Crated	334 lbs	
Height - Crated	35"	
Width - Crated	50"	
Depth - Crated	33"	

^{**}NOTE: Remote units are field wired and come with 6" legs. Refrigerant must be specified at time of order.

We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM).



Worktop Refrigerator Model: WTRD48AHC-4-FIP



ELECTRICAL CONNECTION



Unit pre-wired at factory and include 8' long cord 115/60/1 and include 8 and plug set.



